



US00D667361S

(12) **United States Design Patent**
Bindner et al.

(10) **Patent No.:** **US D667,361 S**

(45) **Date of Patent:** **** Sep. 18, 2012**

(54) **TIRE**

(75) Inventors: **Olivier Francis Bindner**, Yutz (FR);
Alexandre Andre Scharis, Trois-ponts
(BE); **Tony Raymond Gery Deroo**,
Hettange Grande (FR); **Brian Rene**
Bourel, Schieren (LU); **Roland Paul**
Close, Burg-Reuland (BE); **Maurice**
Graas, Reichlange (LU)

(73) Assignee: **The Goodyear Tire & Rubber**
Company, Akron, OH (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/418,220**

(22) Filed: **Apr. 13, 2012**

(51) **LOC (9) Cl.** **12-15**

(52) **U.S. Cl.** **D12/558; D12/563**

(58) **Field of Classification Search** D12/533–567,
D12/593, 599, 900–901; 152/209.1–209.9,
152/209.11–209.19, 209.21–209.28, 455
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D336,455 S *	6/1993	Hammond et al.	D12/558
D389,790 S	1/1998	Himuro	D12/147
D395,627 S *	6/1998	Ball et al.	D12/558
D422,247 S	4/2000	Gerresheim et al.	D12/147
D438,827 S	3/2001	Gerresheim et al.	D12/147
D442,524 S	5/2001	Gerresheim et al.	D12/147
D450,033 S *	11/2001	Graas et al.	D12/563
D452,198 S	12/2001	Heinen et al.	D12/146
D470,100 S *	2/2003	Johenning et al.	D12/563
D471,152 S *	3/2003	Graas et al.	D12/563
D472,201 S *	3/2003	Heinen	D12/558
D488,771 S	4/2004	Villamizar	D12/590
D491,518 S	6/2004	Miyabe et al.	D12/556
D491,885 S *	6/2004	Welbes	D12/558
D495,990 S *	9/2004	Graas	D12/563

D495,991 S *	9/2004	Chatignoux	D12/563
D504,866 S	5/2005	Collette et al.	D12/553
D505,111 S *	5/2005	Allison et al.	D12/563
D505,383 S	5/2005	Ratliff, Jr. et al.	D12/551
D516,998 S *	3/2006	Wang et al.	D12/563
D526,955 S	8/2006	Heinen et al.	D12/549
D526,956 S *	8/2006	Welbes et al.	D12/553
D534,482 S	1/2007	Schmalix et al.	D12/553
D535,247 S	1/2007	Shondel et al.	D12/553
D535,248 S	1/2007	Ashton et al.	D12/553
D559,774 S	1/2008	Kurata	D12/585

(Continued)

Primary Examiner — Stacia Cadmus

(74) *Attorney, Agent, or Firm* — Richard B. O’Planick

(57) **CLAIM**

The ornamental design for a tire, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a tire showing our new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread;

FIG. 2 is a front elevational view thereof;



FIG. 3 is a right side elevational view thereof; the other side being a mirror image thereof;

FIG. 4 is an enlarged fragmentary front elevational view thereof;

FIG. 5 is a perspective view of a second embodiment of a tire showing our new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread and that the opposite side view is a mirror image thereof; and, FIG. 6 is a front elevational view of a second embodiment, it being understood that an enlarged fragmentary view thereof would be substantially identical to that shown in FIG. 4, with the exception of the inclusion of the sidewall in solid lines.

In the drawings, the broken lines showing of the sidewall, inner bead and the peripheral boundary between the tire tread and the sidewall in FIGS. 1 through 4 depict environmental subject matter and form no part of the claimed design.

1 Claim, 6 Drawing Sheets



US D667,361 S

Page 2

U.S. PATENT DOCUMENTS

D574,318 S	8/2008	Ashton et al.	D12/553	D596,109 S	7/2009	de Briey-Terlinden et al.	D12/553
D583,305 S	12/2008	Ashton et al.	D12/553	D596,558 S	7/2009	de Briey-Terlinden	D12/553
D589,435 S	3/2009	Ashton et al.	D12/563	D612,324 S	3/2010	Harvey et al.	D12/551
D591,672 S	5/2009	de Briey-Terlinden et al.	D12/553	D641,306 S	7/2011	Graas et al.	D12/551

* cited by examiner




FIG-1




FIG-2




FIG-3




FIG-4




FIG-5




FIG-6