



US00D668567S

(12) **United States Design Patent**
Dunkin et al.

(10) **Patent No.:** **US D668,567 S**
(45) **Date of Patent:** **** Oct. 9, 2012**

(54) **DISPLAY HOUSING FOR HANDHELD INSPECTION DEVICE**

2009/0109283 A1* 4/2009 Scott et al. 348/65
2009/0322867 A1* 12/2009 Carrey et al. 348/77
2010/0033563 A1* 2/2010 Boehnlein et al. 348/84

(75) Inventors: **Jon R. Dunkin**, Elyria, OH (US);
Edward A. McKiernan, Avon, OH (US);
Sarah A. Golish, Westlake, OH (US);
Christopher L. Lane, Lakewood, OH (US)

OTHER PUBLICATIONS

“IR Thermometer MicroRay IR-100 Non-Contact Infrared Thermometer” RIGID [Catalog], Ridge Tool Company, a subsidiary of Emerson, part of Emerson Professional Tools™, © 2008 RIDGID, Inc., p. 7.20.
“Micro CG-100™ Combustible Gas Sniffer” RIGID [Catalog], Ridge Tool Company, a subsidiary of Emerson, part of Emerson Professional Tools™, © 2008 RIDGID, Inc., p. 7.21.
“SeeSnake® micro™ Inspection Camera”, RIGID [Catalog], Ridge Tool Company, a subsidiary of Emerson, part of Emerson Professional Tools™, © 2008 RIDGID, Inc., pp. 11.14 and 11.15.

(73) Assignee: **Emerson Electric Co.**, St. Louis, MO (US)

(**) Term: **14 Years**

* cited by examiner

(21) Appl. No.: **29/391,463**

Primary Examiner — Antoine D Davis

(22) Filed: **May 9, 2011**

(51) **LOC (9) Cl.** **10-04**

(52) **U.S. Cl.** **D10/78; D10/104**

(58) **Field of Classification Search** D10/78,
D10/104, 46; D16/202; 250/208.1, 330,
250/336.1, 338.1, 339.03, 395, 256; 348/65–68,
348/77, 141, 84, 45, 74; 362/1, 109, 294,
362/373, 399; 713/176; 324/329, 67, 326;
73/623, 865.8, 151; 356/241, 237, 378; 15/324,
15/339; 385/116, 117; 29/729, 592.1, 593;
439/585, 587, 588, 589; 600/109, 129, 131,
600/175, 177; D24/133, 138

(57) **CLAIM**

The ornamental design for a display housing for a handheld inspection device, as shown and described.

See application file for complete search history.

DESCRIPTION

FIG. 1 is a front perspective view of an exemplary handheld inspection device that embodies a display housing in accordance with the principles of the present design;
FIG. 2 is a front perspective view of a first embodiment of the display housing for a handheld inspection device;
FIG. 3 is a front view of the first embodiment of the display housing for a handheld inspection device;
FIG. 4 is a rear view of the first embodiment of the display housing for a handheld inspection device;
FIG. 5 is a top view of the first embodiment of the display housing for a handheld inspection device;
FIG. 6 is a bottom view of the first embodiment of the display housing for a handheld inspection device;
FIG. 7 is a first side view of the first embodiment of the display housing for a handheld inspection device;
FIG. 8 is a second side view of the first embodiment of the display housing for a handheld inspection device;
FIG. 9 is a front perspective view of a second embodiment of the display housing for a handheld inspection device;

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,373,317 A * 12/1994 Salvati et al. 348/65
D559,386 S 1/2008 Pease et al.
D560,804 S 1/2008 Pease et al.
7,758,495 B2* 7/2010 Pease et al. 600/104
D621,732 S * 8/2010 Whitcomb et al. D10/78
7,767,963 B1* 8/2010 Fujii 250/330
7,902,990 B2* 3/2011 Delmonico et al. 340/636.1
D641,270 S * 7/2011 Whitcomb et al. D10/78
8,033,993 B2* 10/2011 Amano et al. 600/160
8,079,951 B2* 12/2011 Yokota 600/120
8,118,733 B2* 2/2012 Scott et al. 600/130
8,142,346 B2* 3/2012 Shoroji et al. 600/110
8,182,416 B1* 5/2012 Hosaka et al. 600/131




FIG. 10 is a front view of the second embodiment of the display housing for a handheld inspection device;
FIG. 11 is a rear view of the second embodiment of the display housing for a handheld inspection device;
FIG. 12 is a top view of the second embodiment of the display housing for a handheld inspection device;
FIG. 13 is a bottom view of the second embodiment of the display housing for a handheld inspection device;
FIG. 14 is a first side view of the second embodiment of the display housing for a handheld inspection device;
FIG. 15 is a second side view of the second embodiment of the display housing for a handheld inspection device;
FIG. 16 is a front perspective view of a third embodiment of the display housing for a handheld inspection device;
FIG. 17 is a front view of the third embodiment of the display housing for a handheld inspection device;

FIG. 18 is a rear view of the third embodiment of the display housing for a handheld inspection device;
FIG. 19 is a top view of the third embodiment of the display housing for a handheld inspection device;
FIG. 20 is a bottom view of the third embodiment of the display housing for a handheld inspection device;
FIG. 21 is a first side view of the third embodiment of the display housing for a handheld inspection device; and,
FIG. 22 is a second side view of the third embodiment of the display housing for a handheld inspection device. It is to be understood that the broken lines shown throughout the drawings are for illustrative purposes only and form no part of the present design.

1 Claim, 19 Drawing Sheets




Fig-1




Fig-2




Fig-3




Fig-4




Fig-6




Fig-5




Fig-7




Fig-8




Fig-9




Fig-10




Fig-11




Fig-12




Fig-13




Fig-14




Fig-15




Fig-16




Fig-17




Fig-18




Fig-20




Fig-19




Fig-21




Fig-22