



US00D669305S

(12) **United States Design Patent**
Smyers(10) **Patent No.:** **US D669,305 S**
(45) **Date of Patent:** **** Oct. 23, 2012**(54) **LID FOR FOOD STORAGE VESSELS**(75) Inventor: **Justin Smyers**, Newport Beach, CA
(US)(73) Assignee: **Snapware Corporation**, Mira Loma,
CA (US)(**) Term: **14 Years**(21) Appl. No.: **29/367,143**(22) Filed: **Aug. 3, 2010**(51) LOC (9) Cl. **07-02**(52) U.S. Cl. **D7/392**(58) **Field of Classification Search** D7/391–392.1,
D7/396.2, 510–511, 541, 629; D9/440, 444,
D9/447, 449–150, 454, 503, 504; D3/273,
D3/282, 302; 215/211, 200, 224, 243; 220/214,
220/324, 326, 711, 715, 719, 784

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

| | | | |
|------------------|---------|------------------|----------|
| 4,625,885 A * | 12/1986 | Nichols | 220/214 |
| D356,256 S * | 3/1995 | Romanoff | D3/282 |
| D452,374 S * | 12/2001 | Kim | D3/302 |
| D455,321 S * | 4/2002 | Jung et al. | D7/629 |
| D481,910 S * | 11/2003 | Kim | D7/629 |
| D483,622 S * | 12/2003 | Kim | D7/629 |
| D484,367 S * | 12/2003 | Kim | D7/629 |
| D490,277 S * | 5/2004 | Kim | D7/629 |
| D493,073 S * | 7/2004 | Kim | D7/629 |
| D500,227 S * | 12/2004 | Seok | D7/392.1 |
| D516,376 S * | 3/2006 | Kim | D7/392.1 |
| D528,357 S * | 9/2006 | Hsu | D7/392.1 |
| D536,571 S * | 2/2007 | Kim | D7/391 |
| D549,519 S * | 8/2007 | Moon et al. | D7/391 |
| D556,517 S * | 12/2007 | Lown et al. | D7/629 |
| D562,083 S * | 2/2008 | Lown et al. | D7/629 |
| D610,878 S * | 3/2010 | Kim | D7/629 |
| D610,879 S * | 3/2010 | Kim | D7/629 |
| D615,821 S * | 5/2010 | Stamper | D7/541 |
| 2004/0084464 A1* | 5/2004 | Koo | 220/784 |
| 2005/0035125 A1* | 2/2005 | Bae | 220/326 |

* cited by examiner

Primary Examiner — Cytnhia M Chin

(74) *Attorney, Agent, or Firm* — Larry K. Roberts(57) **CLAIM**

The ornamental design for a lid for food storage vessels, as shown and described.

DESCRIPTION

This application claims priority under 35 USC Section 120 from application Ser. No. 29/366,916, filed Jul. 30, 2010, the entire contents of which are incorporated by reference herein. FIG. 1 is an isometric view of an embodiment of the design; FIG. 2 is a right side elevation view of the embodiment of FIG. 1, the left side elevation view being identical to the right side elevation view.

FIG. 3 is a front elevation view of the embodiment of FIG. 1, the back elevation view being identical to the front elevation view;

FIG. 4 is a top view of the embodiment of FIG. 1;

FIG. 5 is a bottom view of the embodiment of FIG. 1;

FIG. 6 is an isometric view of another embodiment of the design;

FIG. 7 is a right side elevation view of the embodiment of FIG. 6, the left side elevation view being identical to the right side elevation view.

FIG. 8 is a front elevation view of the embodiment of FIG. 6, the back elevation view being identical to the front elevation view;

FIG. 9 is a top view of the embodiment of FIG. 6;

FIG. 10 is a bottom view of the embodiment of FIG. 6;

FIG. 11 is an isometric view of another embodiment of the design;

FIG. 12 is a right side elevation view of the embodiment of FIG. 11, the left side elevation view being identical to the right side elevation view.

FIG. 13 is a front elevation view of the embodiment of FIG. 11, the back elevation view being identical to the front elevation view;

FIG. 14 is a top view of the embodiment of FIG. 11;

FIG. 15 is a bottom view of the embodiment of FIG. 11;

FIG. 16 is an isometric view of another embodiment of the design;

FIG. 17 is a right side elevation view of the embodiment of FIG. 16, the left side elevation view being identical to the right side elevation view.




FIG. 18 is a front elevation view of the embodiment of FIG. **16**, the back elevation view being identical to the front elevation view;

FIG. 19 is a top view of the embodiment of FIG. **16**;

FIG. 20 is a bottom view of the embodiment of FIG. **16**;

FIG. 21 is an isometric view of another embodiment of the design;

FIG. 22 is a right side elevation view of the embodiment of FIG. **21**, the left side elevation view being identical to the right side elevation view.

FIG. 23 is a front elevation view of the embodiment of FIG. **21**, the back elevation view being identical to the front elevation view;

FIG. 24 is a top view of the embodiment of FIG. **21**;

FIG. 25 is a bottom view of the embodiment of FIG. **21**;

FIG. 26 is an isometric view of another embodiment of the design;

FIG. 27 is a right side elevation view of the embodiment of FIG. **26**, the left side elevation view being identical to the right side elevation view.

FIG. 28 is a front elevation view of the embodiment of FIG. **26**, the back elevation view being identical to the front elevation view;

FIG. 29 is a top view of the embodiment of FIG. **26**; and,

FIG. 30 is a bottom view of the embodiment of FIG. **26**.

The broken lines immediately adjacent the shaded areas represent the bounds of the claim and all other broken lines represent unclaimed portions of the design. None of the broken lines form a part of the claimed design.

1 Claim, 24 Drawing Sheets




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9





FIG. 10






FIG. 12



FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30