



US00D670035S

(12) **United States Design Patent**  
**Mieth et al.**

(10) **Patent No.:** **US D670,035 S**

(45) **Date of Patent:** **\*\* Oct. 30, 2012**

(54) **HEAD RESTRAINT DEVICE**

(76) Inventors: **Bernd S. Mieth**, Westborough, MA (US); **Dirk B. Mieth**, Southborough, MA (US)

(\*\*) Term: **14 Years**

(21) Appl. No.: **29/426,310**

(22) Filed: **Jul. 3, 2012**

(51) **LOC (9) Cl.** ..... **02-03**

(52) **U.S. Cl.** ..... **D29/102**

(58) **Field of Classification Search** ..... D29/102-107, D29/122, 108-111; 2/175.4, 200.1, 8.2, 2/6.6, 6.7, 410, 411, 417, 421, 424, 425, 2/468, 9, 418, 209.3; 359/642, 815; 362/105, 362/106; 297/393, 464; D24/190-191; 128/857-858, 869, 876; 602/17  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,796,866	A *	6/1957	Cohen	128/869
4,182,322	A	1/1980	Miller	
4,339,151	A	7/1982	Riggs	
4,560,201	A	12/1985	Scott	
4,565,408	A	1/1986	Palley	
4,707,031	A	11/1987	Meistrell	
5,242,377	A *	9/1993	Boughner et al.	602/17
5,378,042	A *	1/1995	Daneshvar	297/393
D363,547	S *	10/1995	Huber	D24/191
6,266,825	B1	7/2001	Floyd	
6,607,245	B1	8/2003	Scher	
6,799,802	B1 *	10/2004	Moran	297/393
6,805,403	B2	10/2004	Buch	
6,886,186	B2	5/2005	Jansen	
7,004,545	B2	2/2006	Miller	
7,628,456	B1 *	12/2009	Swartz	297/464
7,637,261	B2	12/2009	Sharp	
D615,453	S	5/2010	Spears	
7,832,802	B2	11/2010	Ehlers et al.	

2004/0026979 A1 2/2004 Haddon  
2009/0271904 A1 11/2009 Bentley  
2010/0283310 A1 11/2010 Blackwood  
2010/0308630 A1 12/2010 Davis  
2011/0043025 A1 2/2011 Park

(Continued)

*Primary Examiner* — Ruth McInroy

(74) *Attorney, Agent, or Firm* — Kriegsmann & Kriegsmann

(57) **CLAIM**

The ornamental design for a head restraint device, as shown and described.

**DESCRIPTION**

FIG. 1 is a front perspective view of a head restraint device showing my new design, the head restraint device being shown with the adjustable head strap disposed in a connected state;

FIG. 2 is a front perspective view of the head restraint device shown in FIG. 1, the head restraint device being shown with the adjustable head strap disposed in a disconnected state;

FIG. 3 is a front view of the head restraint device shown in FIG. 1;

FIG. 4 is a rear view of the head restraint device shown in FIG. 1;

FIG. 5 is a left end view of the head restraint device shown in FIG. 1;

FIG. 6 is a right end view of the head restraint device shown in FIG. 1;


FIG. 7 is a top view of the head restraint device shown in FIG. 1;

FIG. 8 is a bottom view of the head restraint device shown in FIG. 1; and,

FIG. 9 is a right end view of the head restraint device shown in FIG. 1, the device being shown on a person.

The person shown in broken lines in FIG. 9 forms no part of the claimed design. The dashed lines on the head restraint device represent conventional stitching.

**1 Claim, 5 Drawing Sheets**





# US D670,035 S


Page 2

---


## U.S. PATENT DOCUMENTS

2011/0101761 A1	5/2011	Demaras		2011/0204696 A1	8/2011	Koehler
2011/0132379 A1*	6/2011	Lee .....	128/857	2011/0271421 A1	11/2011	Vahey
						* cited by examiner







**FIG. 3**




**FIG. 4**




**FIG. 5**



**FIG. 6**



*FIG. 7*



*FIG. 8*

**FIG. 9**

