



US00D671246S

(12) **United States Design Patent**
Inoue

(10) **Patent No.:** **US D671,246 S**

(45) **Date of Patent:** **** Nov. 20, 2012**

(54) **ILLUMINATION DEVICE FOR INSPECTION**

(75) Inventor: **Yoshihiro Inoue**, Kyotanabe (JP)

(73) Assignee: **CCS Inc.**, Kyoto-shi (JP)

(**) Term: **14 Years**

(21) Appl. No.: **29/379,799**

(22) Filed: **Nov. 24, 2010**

(30) **Foreign Application Priority Data**

May 27, 2010 (JP) 2010-013085
May 27, 2010 (JP) 2010-013106

(51) **LOC (9) Cl.** **26-05**

(52) **U.S. Cl.** **D26/24**

(58) **Field of Classification Search** D26/24,
D26/37, 51, 58, 72, 85, 88, 89, 91, 93; 362/600,
362/601, 602, 603, 612, 632, 572, 576, 577,
362/33, 133, 145, 146, 147, 153, 311.02
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

| | | | | | |
|--------------|------|---------|-----------------|-------|---------|
| D221,583 | S * | 8/1971 | Donato | | D26/67 |
| D243,035 | S * | 1/1977 | Kohlenstein | | D26/24 |
| D397,470 | S * | 8/1998 | Bassford et al. | | D26/67 |
| 6,755,550 | B1 * | 6/2004 | Lackey | | 362/147 |
| D536,463 | S * | 2/2007 | Chiang | | D26/24 |
| D558,382 | S * | 12/2007 | Cesaro | | D26/86 |
| D603,547 | S * | 11/2009 | Starck | | D26/72 |
| 7,731,391 | B2 * | 6/2010 | Messina et al. | | 362/235 |
| D625,877 | S * | 10/2010 | Hsu et al. | | D26/80 |
| D643,964 | S * | 8/2011 | Heyrman | | D26/85 |
| 8,092,034 | B2 * | 1/2012 | Zarian et al. | | 362/145 |
| D663,876 | S * | 7/2012 | Tomita et al. | | D26/37 |
| 2012/0020112 | A1 * | 1/2012 | Fisher et al. | | 362/608 |

* cited by examiner

Primary Examiner — Angela J Lee

(74) *Attorney, Agent, or Firm* — Alleman Hall McCoy Russell & Tuttle LLP

(57) **CLAIM**

The ornamental design for an illumination device for inspection, as shown and described.

DESCRIPTION

FIG. 1 is a front view of a first embodiment of an illumination device for inspection, with an associated electric cable shown in dashed lines.

FIG. 2 is a rear view of the illumination device of FIG. 1.

FIG. 3 is a right side view of the illumination device of FIG. 1.

FIG. 4 is a left side view of the illumination device of FIG. 1.

FIG. 5 is a top view of the illumination device of FIG. 1.

FIG. 6 is a bottom view of the illumination device of FIG. 1.

FIG. 7 is a front perspective view of the illumination device of FIG. 1.

FIG. 8 is a top view of the illumination device of FIG. 1, omitting the electric cable.

FIG. 9 is a front view of a second embodiment of an illumination device for inspection, with an associated electric cable shown in dashed lines.

FIG. 10 is a rear view of the illumination device of FIG. 9.

FIG. 11 is a right side view of the illumination device of FIG. 9.

FIG. 12 is a left side view of the illumination device of FIG. 9.

FIG. 13 is a top view of the illumination device of FIG. 9.


FIG. 14 is a bottom view of the illumination device of FIG. 9.

FIG. 15 is a front perspective view showing the illumination device of FIG. 9; and,

FIG. 16 is a top view of the illumination device of FIG. 9, omitting the electric cable.

The broken lines shown in the drawings represent an electric cable and form no part of the claimed design.

1 Claim, 8 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16