

US00D672263S

(12) **United States Design Patent**
Reiter

(10) **Patent No.:** **US D672,263 S**
(45) **Date of Patent:** **** Dec. 11, 2012**

(54) **SIGNALING DEVICE**

DESCRIPTION

(76) Inventor: **Spencer Alan Reiter**, DeRidder, LA (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/370,598**

(22) Filed: **Aug. 9, 2010**

(51) **LOC (9) Cl.** **10-05**

(52) **U.S. Cl.** **D10/109.1**

(58) **Field of Classification Search** D10/104.1,
D10/109.1, 109.2, 111; 63/1.12; 359/515;
116/20

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,698,595	A *	1/1955	Morgan	116/20
2,698,596	A *	1/1955	Morgan	116/20
4,024,828	A *	5/1977	Knoll et al.	116/20
D334,149	S *	3/1993	Dobbs	D10/109.1
5,617,247	A *	4/1997	Rowland	359/515
2009/0173104	A1 *	7/2009	Shunnarah	63/1.12

* cited by examiner

Primary Examiner — George D Kirschbaum

(74) *Attorney, Agent, or Firm* — R. Tracy Crump

(57) **CLAIM**

I claim the ornamental design of the signaling device, as shown and described.

FIG. 1 is a perspective view of the signaling device showing my new design in a closed position;

FIG. 2 is a top view of the signaling device thereof in a closed position;

FIG. 3 is a bottom view of the signaling device thereof in a closed position;

FIG. 4 is a left side view of the signaling device thereof in a closed position;

FIG. 5 is a right side view of the signaling device thereof in a closed position;

FIG. 6 is a front view of the signaling device thereof in a closed position;

FIG. 7 is a rear view of the signaling device thereof in a closed position;

FIG. 8 is a perspective view of the signaling device showing my new design in an open position;

FIG. 9 is a top view of the signaling device thereof in an open position;

FIG. 10 is a right side view of the signaling device thereof in an open position;



FIG. 11 is a left side view of the signaling device thereof in an open position;

FIG. 12 is a bottom view of the signaling device thereof in an open position;

FIG. 13 is a front view of the signaling device thereof in an open position; and,

FIG. 14 is a rear view of the signaling device thereof in an open position.

1 Claim, 6 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14