



US00D672897S

(12) **United States Design Patent**
Guercio et al.

(10) **Patent No.:** **US D672,897 S**

(45) **Date of Patent:** **** Dec. 18, 2012**

(54) **GOOSENECK LED FIXTURE**

D332,504 S 1/1993 Ewing et al.

D370,289 S 5/1996 Deron

6,203,176 B1 3/2001 Gordin

(Continued)

(75) Inventors: **Vincenzo Guercio**, Wallkill, NY (US);
Wengang Gao, Ningbo (CN)

(73) Assignee: **RAB Lighting Inc.**, Northvale, NJ (US)

Primary Examiner — Susan M Lee

Assistant Examiner — Linda G. Brooks

(**) Term: **14 Years**

(74) *Attorney, Agent, or Firm* — Stewart & Irwin, P.C.;
Dennis S. Schell

(21) Appl. No.: **29/425,574**

(57) **CLAIM**

(22) Filed: **Jun. 25, 2012**

The ornamental design for a gooseneck LED fixture, as shown and described.

Related U.S. Application Data

DESCRIPTION

(62) Division of application No. 29/391,321, filed on May 6, 2011, now Pat. No. Des. 664,694.

(51) **LOC (9) Cl.** **26-05**

(52) **U.S. Cl.** **D26/62**

(58) **Field of Classification Search** D26/60-66,
D26/107, 118, 72, 85, 87, 92; 362/269, 270,
362/277, 282, 285, 287, 427, 145, 147, 800,
362/319, 322, 351, 352, 355, 278, 418, 419,
362/432, 449

See application file for complete search history.

FIG. 1 is a top perspective view of a first embodiment of the new design with a first semi-spherical shade as shown; FIG. 2 is a front view of the first embodiment; FIG. 3 is a right view of the first embodiment; FIG. 4 is a left view of the first embodiment; FIG. 5 is a rear view of the first embodiment; FIG. 6 is a top view of the first embodiment; FIG. 7 is a bottom view of the first embodiment; FIG. 8 is a bottom perspective view of a first embodiment; and,

(56) **References Cited**


U.S. PATENT DOCUMENTS

D42,961 S	9/1912	D'Olier, Jr.
D56,547 S	11/1920	Yates
D59,056 S	9/1921	Benjamin
D83,058 S	1/1931	O'Neil
D90,240 S	7/1933	Ender
D106,774 S	7/1937	Phillips
3,636,339 A	1/1972	Osborne, Jr.
3,639,751 A	2/1972	Pichel
4,654,768 A	3/1987	Dryman
4,761,721 A	8/1988	Willing

FIG. 9 is a left view of a second embodiment of the new design, comprising the first embodiment of FIGS. 1-8 with the first semi-spherical shade replaced with a second semi-spherical shade as shown, which has the same shape as the first semi-spherical shade as shown in FIGS. 1-8, but is configured to couple with the LED housing at an different offset angle as can be understood by comparing FIGS. 4 and 9.

The broken lines shown in the drawings are for the purpose of illustrating portions of the article that form no part of the claimed design. The lamp arm is shown broken away in FIGS. 1, 3, 4 and 6-9 to show that no particular length is claimed.

1 Claim, 9 Drawing Sheets



US D672,897 S

Page 2

U.S. PATENT DOCUMENTS

D516,229 S	2/2006	Tang	D586,498 S	2/2009	Wu et al.
D528,673 S	9/2006	Maxik et al.	D590,077 S	4/2009	Grajcar
D544,127 S	6/2007	Posey	D590,977 S	4/2009	Mullen
D547,466 S	7/2007	Lo	D601,276 S	9/2009	Grajcar
D549,380 S	8/2007	Guercio	D601,279 S	9/2009	Ou et al.
D566,300 S	4/2008	Lo	D610,723 S	2/2010	Grajcar
D573,294 S	7/2008	Chan et al.	D616,576 S	5/2010	Wang et al.
D581,583 S	11/2008	Peng	D617,014 S	6/2010	Foo
D582,579 S	12/2008	Tsai et al.	D627,920 S	11/2010	Hanna et al.
			D632,833 S	2/2011	Lee




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9