



US00D678094S

(12) **United States Design Patent**  
**Rodrig et al.**

(10) **Patent No.:** **US D678,094 S**  
(45) **Date of Patent:** **\*\* Mar. 19, 2013**

(54) **COMBINATION TIRE PRESSURE AND TREAD DEPTH GAUGE**

(75) Inventors: **Steven Rodrig**, Hillsborough, NJ (US);  
**Steven Petrucelli**, Cranbury, NJ (US);  
**Mark Kuskovsky**, Monroe Township, NJ (US)

(73) Assignee: **Measurement Ltd.**, Grand Cayman (KY)

(\*\*) Term: **14 Years**

(21) Appl. No.: **29/405,955**

(22) Filed: **Nov. 8, 2011**

**Related U.S. Application Data**

(62) Division of application No. 29/367,712, filed on Aug. 12, 2010, now Pat. No. Des. 648,236.

(51) **LOC (9) Cl.** ..... **10-04**

(52) **U.S. Cl.** ..... **D10/86**

(58) **Field of Classification Search** ..... D10/86;  
73/732, 744, 742, 717, 741, 146.3, 146.8

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

4,631,831	A	12/1986	Bacher et al.	
4,970,894	A	11/1990	Huang	
D317,880	S	7/1991	Meehan	
D366,846	S	* 2/1996	Handfield et al.	D10/86
D390,140	S	* 2/1998	Germanton	D10/86
D395,835	S	* 7/1998	Okuyama et al.	D10/85
5,883,306	A	3/1999	Hwang	
5,895,845	A	4/1999	Burger	
D409,509	S	5/1999	Petrucelli et al.	
D409,931	S	5/1999	Petrucelli et al.	
5,987,978	A	11/1999	Whitehead	
D440,893	S	4/2001	Van Zeyl	
D440,894	S	4/2001	Van Zeyl	
D440,895	S	4/2001	Van Zeyl	
D441,674	S	5/2001	Van Zeyl	
D447,970	S	9/2001	Cappiello et al.	
D450,257	S	11/2001	Bressler et al.	
D455,666	S	4/2002	Cappiello et al.	

D459,257	S	6/2002	Petrucelli	
D459,668	S	7/2002	Petrucelli	
D462,627	S	9/2002	Petrucelli	
6,634,223	B2	10/2003	Hartmann et al.	
7,010,969	B1	3/2006	Huang	
D522,894	S	6/2006	Stowers et al.	
D526,229	S	8/2006	Stowers et al.	
D526,589	S	8/2006	Stowers et al.	
D526,922	S	8/2006	Stowers et al.	
D534,092	S	12/2006	Kuskovsky	
D564,383	S	3/2008	Petrucelli et al.	
D596,970	S	7/2009	Petrucelli	
D603,733	S	11/2009	Stowers et al.	
D606,435	S	* 12/2009	Zheng	D10/86
D631,766	S	2/2011	Petrucelli	
D631,768	S	2/2011	Petrucelli et al.	
7,928,960	B2	* 4/2011	Baldo et al.	345/156

\* cited by examiner

*Primary Examiner* — Antoine D Davis

(74) *Attorney, Agent, or Firm* — Howard IP Law Group, PC

(57) **CLAIM**

The ornamental design for a combination tire pressure and tread depth gauge, as shown and described.

**DESCRIPTION**

FIG. 1 is a perspective view of a combination tire pressure and tread depth gauge showing our new design, according to an embodiment of the invention;

FIG. 2 is a top view of the combination tire pressure and tread depth gauge of FIG. 1;

FIG. 3 is a right side elevational view of the combination tire pressure and tread depth gauge of FIG. 1;

FIG. 4 is a front elevational view of the combination tire pressure and tread depth gauge of FIG. 1;

FIG. 5 is a rear elevational view of the combination tire pressure and tread depth gauge of FIG. 1;

FIG. 6 is a left side elevational view of the combination tire pressure and tread depth gauge of FIG. 1;

FIG. 7 is a bottom view of the combination tire pressure and tread depth gauge of FIG. 1;

FIG. 8 is a perspective view of the combination tire pressure and tread depth gauge of FIG. 1, shown with a rod for measuring tread depth in an extended position;




FIG. 9 is a perspective view of a combination tire pressure and tread depth gauge, showing our new design, according to another embodiment of the invention, having the same front elevational view, rear elevational view, and bottom view as set forth in FIGS. 4, 5 and 7, respectively;

FIG. 10 is a top view of the combination tire pressure and tread depth gauge of FIG. 9;

FIG. 11 is a right side elevational view of the combination tire pressure and tread depth gauge of FIG. 9;

FIG. 12 is a left side elevational view of the combination tire pressure and tread depth gauge of FIG. 9;

FIG. 13 is a perspective view of a combination tire pressure and tread depth gauge, showing our new design, according to another embodiment of the invention, having the same right side elevational view, front elevational view, rear elevational view, left side elevational view, and bottom view as set forth in FIGS. 3-7, respectively;

FIG. 14 is a top view of the combination tire pressure and tread depth gauge of FIG. 13;


FIG. 15 is a perspective view of a combination tire pressure and tread depth gauge, showing our new design, according to another embodiment of the invention, having the same right side elevational view, front elevational view, rear elevational view, left side elevational view, and bottom view as set forth in FIGS. 3-7, respectively;

FIG. 16 is a top view of the combination tire pressure and tread depth gauge of FIG. 15;


FIG. 17 is a perspective view of a combination tire pressure and tread depth gauge, showing our new design, according to another embodiment of the invention, having the same front elevational view, rear elevational view, bottom view, and left side elevational view as set forth in FIGS. 4, 5, 7 and 12, respectively; and,

FIG. 18 is a right side elevational view of the combination tire pressure and tread depth gauge of FIG. 17.


**1 Claim, 7 Drawing Sheets**




*Fig. 1*




*Fig. 2*




*Fig. 3*




*Fig. 4*



*Fig. 5*




*Fig. 6*




*Fig. 7*







*Fig. 8*




*Fig. 9*




*Fig. 10*




*Fig. 11*




*Fig. 12*




*Fig. 13*



*Fig. 14*




*Fig. 15*




*Fig. 16*





*Fig. 17*



*Fig. 18*