

US00D678921S

(12) **United States Design Patent**
Rinderer et al.

(10) **Patent No.:** **US D678,921 S**

(45) **Date of Patent:** **** Mar. 26, 2013**

(54) **OPEN-FRONT REFRIGERATED COOLER**

(75) Inventors: **Matthias Rinderer**, Fuschl Am See (AT); **Jürgen Brenneis**, Pinsdorf (AT); **Toby McDell**, Fuschl Am See (AT)

(73) Assignee: **Red Bull GmbH**, Fuschl Am See (AU)

(**) Term: **14 Years**

(21) Appl. No.: **29/395,662**

(22) Filed: **Mar. 8, 2012**

(51) **LOC (9) Cl.** **15-07**

(52) **U.S. Cl.** **D15/81**

(58) **Field of Classification Search** D15/79,
D15/81, 83; D6/470-472; 62/246-255,
62/331, 337, 440-449, 3.6; 312/114, 116,
312/236, 138.1, 401-405

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D202,081 S *	8/1965	Zaslovsky et al.	D6/470
3,218,822 A *	11/1965	Bently et al.	62/256
D209,722 S *	12/1967	Mangini	D6/471
D280,790 S *	10/1985	Kooy	D6/471
4,608,776 A *	9/1986	Kooy	312/116
D348,790 S *	7/1994	Fujii	D6/479
D352,850 S *	11/1994	Fujii	D6/479
D362,137 S *	9/1995	Fujii	D6/479
D386,502 S *	11/1997	Sholl	D15/79
D427,210 S *	6/2000	Tsukida	D15/83
D458,946 S *	6/2002	Upton et al.	D15/79
D477,335 S *	7/2003	Upton et al.	D15/79
D496,053 S *	9/2004	Wetzel	D15/79
D510,367 S *	10/2005	Yamashita et al.	D15/79
D514,600 S *	2/2006	Yamashita et al.	D15/79
D515,595 S *	2/2006	Jorgensen	D15/81
D515,596 S *	2/2006	Jorgensen	D15/81
D585,911 S *	2/2009	Miyabayashi et al.	D15/79
D589,537 S *	3/2009	Terada et al.	D15/81
D589,538 S *	3/2009	Kumazawa et al.	D15/81
D593,138 S *	5/2009	Howell	D15/81
D594,482 S *	6/2009	Roekens et al.	D15/81
D662,114 S *	6/2012	Deproost	D15/81

* cited by examiner

Primary Examiner — Mitchell Siegel

(74) *Attorney, Agent, or Firm* — TechMark a Law Corporation; Martin R. Greenstein

(57) **CLAIM**

The ornamental design for an open front refrigerated cooler, as shown as described.

DESCRIPTION

FIG. 1 is a top view of the open front refrigerated cooler according to the present invention, with the front blind in the down position;

FIG. 2 is a back view of the open front refrigerated cooler as shown in FIG. 1;

FIG. 3 is a front view of the open front refrigerated cooler as shown in FIG. 1;

FIG. 4 is a front elevational view of the open front refrigerated cooler as shown in FIG. 1;

FIG. 5 is a right side view of the open front refrigerated cooler as shown in FIG. 1;

FIG. 6 is a left side view of the open front refrigerated cooler as shown in FIG. 1;


FIG. 7 is a top view of the open front refrigerated cooler as shown in FIG. 1, with the front blind in the up position, covering the open front;

FIG. 8 is a front view of the open front refrigerated cooler as shown in FIG. 1, with the front blind in the up position, covering the open front; and,

FIG. 9 is a front elevational view of the open front refrigerated cooler as shown in FIG. 1, with the front blind in the up position, covering the open front.

The claimed second embodiment of the design of the present invention includes registered trademarks RED BULL, as seen on the right side view, left side view, front view, and front elevational, the Double Bull Device as seen on the front view and front elevational view, both of which are owned by Red Bull GmbH.

1 Claim, 9 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5



FIG. 6




FIG. 7




FIG. 8



FIG. 9