



US00D680063S

(12) **United States Design Patent**
Sasada

(10) **Patent No.:** **US D680,063 S**

(45) **Date of Patent:** **** Apr. 16, 2013**

(54) **BATTERY**

(75) Inventor: **Motohiro Sasada**, Sumoto (JP)

(73) Assignee: **SANYO Electric Co., Ltd.**,
Moriguchi-shi, Osaka (JP)

(**) Term: **14 Years**

(21) Appl. No.: **29/427,186**

(22) Filed: **Jul. 16, 2012**

(30) **Foreign Application Priority Data**

Jan. 18, 2012 (JP) 2012-000824

(51) **LOC (9) Cl.** **13-02**

(52) **U.S. Cl.**
USPC **D13/103**; D13/108

(58) **Field of Classification Search** D13/102–110,
D13/118–119, 184; 429/96–100, 163, 176;
320/107–115

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D519,918 S *	5/2006	Wilson et al.	D13/103
D599,738 S *	9/2009	Amidei et al.	D13/110
7,746,029 B2 *	6/2010	Toya	320/107
D625,721 S	10/2010	Ferber et al.		
D628,153 S *	11/2010	Fujii et al.	D13/108
D628,535 S *	12/2010	Cheng	D13/108
D656,096 S *	3/2012	Sasada et al.	D13/108
D659,094 S *	5/2012	Brand et al.	D13/108
D663,684 S *	7/2012	Yang	D13/108

D663,685 S *	7/2012	Yang	D13/108
D665,733 S *	8/2012	Petrie et al.	D13/107
D672,309 S *	12/2012	Tien	D13/108

* cited by examiner

Primary Examiner — Rosemary K Tarcza

(74) *Attorney, Agent, or Firm* — Westerman, Hattori,
Daniels & Adrian, LLP

(57) **CLAIM**

The ornamental design for a battery, as shown and described.

DESCRIPTION

FIG. 1 is a right front perspective view of a battery, showing my new design;

FIG. 2 is a right rear perspective view thereof;

FIG. 3 is a front elevational view thereof;

FIG. 4 is a rear elevational view thereof;

FIG. 5 is a top plan view thereof;

FIG. 6 is a bottom plan view thereof;

FIG. 7 is a right side elevational view thereof;

FIG. 8 is a left side elevational view thereof;

FIG. 9 is a cross-sectional view taken along line 9-9 of FIG. 5;

FIG. 10 is a cross-sectional view taken along line 10-10 of FIG. 3;

FIG. 11 is a right front perspective view thereof, showing the connector and cable portion in the undocked state;


FIG. 12 is a right front perspective view thereof, showing the connector and cable portion in the undocked state;

FIG. 13 is a perspective view showing the battery in use, wherein the cable portion is plugged into an electronic device; and,

FIG. 14 is a perspective view showing the battery in use, wherein an adapter is plugged into the battery for charging.

The broken lines illustrate environmental structure only and form no part of the claimed design.

1 Claim, 12 Drawing Sheets






FIG.1




FIG.2




FIG. 3




FIG.4




FIG. 5




FIG. 6




FIG. 8




FIG. 7




FIG.9




FIG. 10




FIG.11




FIG.12




FIG.13




FIG. 14