



US00D680458S

(12) **United States Design Patent**
Corso et al.

(10) **Patent No.:** **US D680,458 S**

(45) **Date of Patent:** **** Apr. 23, 2013**

(54) **WIRELESS GLASS BREAK DETECTOR**

(75) Inventors: **Daniel Anthony Corso**, Macedon, NY (US); **James Bruce Thornton**, Webster, NY (US); **Michael Earl Reimer**, Batavia, NY (US)

(73) Assignee: **Robert Bosch GmbH**, Stuttgart (DE)

(**) Term: **14 Years**

(21) Appl. No.: **29/416,414**

(22) Filed: **Mar. 21, 2012**

(51) **LOC (9) Cl.** **10-05**

(52) **U.S. Cl.**
USPC **D10/104.1**

(58) **Field of Classification Search** D10/104.1,
D10/106.1-106.7; D13/158, 159, 172, 176;
D14/348, 364, 356, 314, 215, 214, 300, 349;
D9/414, 424, 425; 361/726, 816

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D658,647 S * 5/2012 Tsai D14/356
2012/0139671 A1* 6/2012 Gilmore 335/151

* cited by examiner

Primary Examiner — George D Kirschbaum

(74) *Attorney, Agent, or Firm* — Taft Stettinius & Hollister LLP; Keith Swedo

(57) **CLAIM**

The ornamental design for the wireless glass break detector, as shown and described.

DESCRIPTION

FIG. 1 is top right perspective view of the wireless glass break detector;

FIG. 2 is a front view thereof;

FIG. 3 is a rear view thereof;

FIG. 4 is a right side view thereof;



FIG. 5 is a left side view thereof;

FIG. 6 is a top view thereof; and,

FIG. 7 is a bottom view thereof.

The broken line showing of openings, controls and mounting hardware is included for the purpose of illustrating portions of the “article” and forms no part of the claimed design.

1 Claim, 5 Drawing Sheets






Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7