



US00D683142S

(12) **United States Design Patent**
Goldberg

(10) **Patent No.:** **US D683,142 S**

(45) **Date of Patent:** **** May 28, 2013**

(54) **VEHICLE SAFETY SEAT**

(71) Applicant: **Ely Goldberg**, Dollard Des Ormeaux
(CA)

(72) Inventor: **Ely Goldberg**, Dollard Des Ormeaux
(CA)

(**) Term: **14 Years**

(21) Appl. No.: **29/434,284**

(22) Filed: **Oct. 11, 2012**

(51) **LOC (9) Cl.** **06-01**

(52) **U.S. Cl.**
USPC **D6/333**

(58) **Field of Classification Search**

USPC D6/333-336, 339-341, 344, 381,
D6/491, 500-502; 297/250.1, 255, 256.15,
297/183.1-183.4, 184.15, 184.17, 256.16;
D12/129-130, 133; 5/94, 98.2, 103-104,
5/655, 655.3; D21/419; 280/30-31

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

| | | | | | |
|------------|---|---------|--------------------|-------|--------|
| D262,242 S | * | 12/1981 | Molnar | | D6/333 |
| D338,343 S | | 8/1993 | Grange | | |
| D360,307 S | * | 7/1995 | Kain | | D6/333 |
| D383,316 S | * | 9/1997 | Kain | | D6/333 |
| D453,631 S | * | 2/2002 | Kassai et al. | | D6/333 |
| D461,646 S | * | 8/2002 | Kain | | D6/333 |
| D537,640 S | | 3/2007 | Spence et al. | | |
| D626,758 S | * | 11/2010 | Hartenstine et al. | | D6/339 |
| D630,448 S | * | 1/2011 | Xu et al. | | D6/333 |
| D632,501 S | | 2/2011 | Cymbalski et al. | | |
| D636,190 S | | 4/2011 | Werschmidt et al. | | |
| D653,463 S | | 2/2012 | Hartenstine et al. | | |
| D655,925 S | | 3/2012 | Hartenstine et al. | | |
| D661,500 S | | 6/2012 | Hutchinson et al. | | |
| D662,720 S | * | 7/2012 | Gillett et al. | | D6/333 |

OTHER PUBLICATIONS

United States Patent and Trademark Office; Notice of Allowance dated Dec. 20, 2012 issued in respect of U.S. Appl. No. 29/434,288; 6 pages.

* cited by examiner

Primary Examiner — Caron D Veynar

Assistant Examiner — Abraham Bahta

(74) *Attorney, Agent, or Firm* — Norton Rose Canada LLP

(57) **CLAIM**

The ornamental design for a vehicle safety seat, as shown and described.

DESCRIPTION

FIG. 1 is a top, front, and left side perspective view of a vehicle safety seat showing our new design;

FIG. 2 is a front elevation view thereof;

FIG. 3 is a top plan view thereof;

FIG. 4 is a left side elevation view thereof;

FIG. 5 is a right side elevation view thereof;

FIG. 6 is a rear elevation view thereof;

FIG. 7 is a bottom plan view thereof;

FIG. 8 is a top, front, and left side perspective view of a vehicle safety seat according to our design, with a seat drawer in an open position;

FIG. 9 is a front elevation view of the vehicle safety seat of FIG. 8;

FIG. 10 is a top plan view of the vehicle safety seat of FIG. 8;

FIG. 11 is a left side elevation view of the vehicle safety seat of FIG. 8;



FIG. 12 is a right side elevation view of the vehicle safety seat of FIG. 8;

FIG. 13 is a rear elevation view of the vehicle safety seat of FIG. 8; and,

FIG. 14 is a bottom plan view of the vehicle safety seat of FIG. 8.

The broken lines shown throughout the drawing views are for illustrative purposes only and form no part of the claimed design.

1 Claim, 8 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14