



US00D685380S

(12) **United States Design Patent**
Richter

(10) **Patent No.:** **US D685,380 S**

(45) **Date of Patent:** **** Jul. 2, 2013**

- (54) **APPARATUS HOLDER**
- (71) Applicant: **Harald Richter**, Engelbrand (DE)
- (72) Inventor: **Harald Richter**, Engelbrand (DE)
- (**) Term: **14 Years**
- (21) Appl. No.: **29/435,758**
- (22) Filed: **Oct. 28, 2012**
- (51) **LOC (9) Cl.** **08-07**
- (52) **U.S. Cl.**
USPC **D14/447; D14/253**
- (58) **Field of Classification Search**
USPC D14/432, 433, 434, 439, 440, 451,
D14/452, 239, 217, 224.1, 251, 252, 253,
D14/457, 458, 459, 460, 461; D6/406.1,
D6/406.2, 406.3, 406.4, 406.5, 406.6;
361/679.06, 679.21, 679.22, 679.24, 679.26,
361/679.27, 679.28, 679.3, 679.55, 679.56,
361/709; 248/917-924, 133, 136, 139, 150,
248/176.1, 188.6
See application file for complete search history.

- D603,322 S * 11/2009 Nicieja D12/415
- D606,065 S * 12/2009 Rihu D14/253
- D626,953 S * 11/2010 Wilson D14/252
- D667,003 S * 9/2012 Richter D14/253

* cited by examiner

Primary Examiner — Angela J Lee

(74) *Attorney, Agent, or Firm* — Klaus J Bach

(57) **CLAIM**

The ornamental design for an apparatus holder, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of an apparatus holder;
 FIG. 2 is a front view of the apparatus holder shown in FIG. 1,
 FIG. 3 is a top end view of the apparatus holder shown in FIG. 2,
 FIG. 4 is a bottom end view of the apparatus holder shown in FIG. 2,
 FIG. 5 is a left end view of the apparatus holder shown in FIG. 2,
 FIG. 6 is a right end view of the apparatus holder shown in FIG. 2; and,
 FIG. 7 is a rear view of the apparatus holder as shown in FIG. 2.

The apparatus holder is used for supporting for example a cell phone on a support device. The side brackets are position-adjustable and lockable in selected positions to accommodate the width of an apparatus. The side brackets are spring-biased outwardly and can be moved inwardly against the spring bias into engagement with the apparatus and releasably locked in an appropriate position.


The broken lines shown in the drawings represent portions of the apparatus holder that form no part of the claimed design.

(56) **References Cited**

U.S. PATENT DOCUMENTS

- D390,849 S * 2/1998 Richter et al. D14/253
- D431,250 S * 9/2000 Richter D14/447
- D456,024 S * 4/2002 Richter D14/434
- D470,146 S * 2/2003 Tan et al. D14/432
- D521,990 S * 5/2006 Richter D14/253
- D529,905 S * 10/2006 Richter D14/253
- D530,713 S * 10/2006 Richter D14/253
- D535,988 S * 1/2007 Kettula et al. D14/253
- D566,118 S * 4/2008 Brassard D14/434
- D586,795 S * 2/2009 Richter D14/253

1 Claim, 5 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7