



US00D686987S

(12) **United States Design Patent**
Vanstone et al.

(10) **Patent No.:** **US D686,987 S**
(45) **Date of Patent:** **** Jul. 30, 2013**

(54) **SINGLE SLOT USB BATTERY CHARGER**

(75) Inventors: **Mark Vanstone**, Camarillo, CA (US);
Frank Nigro, Valencia, CA (US)

(73) Assignee: **Advanced Bionics AG**, Staefa (CH)

(**) Term: **14 Years**

(21) Appl. No.: **29/399,403**

(22) Filed: **Aug. 12, 2011**

(51) **LOC (9) Cl.** **13-02**

(52) **U.S. Cl.**
USPC **D13/108**

(58) **Field of Classification Search**

USPC D13/107-110, 118-119, 133, 146-147,
D13/184, 199; D14/217, 251, 253, 432-435,
D14/435.1, 436, 480.1, 480.3, 480.4;
320/107-115; 710/300, 301; 439/131, 135-147
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D471,516 S 3/2003 Tsay et al.
D511,519 S * 11/2005 Bone et al. D14/480.1
7,003,356 B2 2/2006 Tsukamoto et al.
D538,223 S 3/2007 Yang
D544,479 S * 6/2007 Chen D14/480.4
D579,933 S * 11/2008 Deguchi D14/480.1
D589,889 S * 4/2009 Wu et al. D13/147
D638,430 S * 5/2011 Lee et al. D14/435.1
D651,211 S * 12/2011 Lee et al. D14/435.1
D659,144 S * 5/2012 Lee et al. D14/435.1
D659,145 S * 5/2012 Lee et al. D14/435.1

D671,123 S * 11/2012 Ni et al. D14/480.1
D673,908 S * 1/2013 Koch D13/108
D675,630 S * 2/2013 Ni et al. D14/480.1
2001/0019254 A1 * 9/2001 Lavender 320/107

OTHER PUBLICATIONS

Auria(R) PowerCel(TM) Charger Instruction Guide 9055231-001
Rev B (c)2009 Advanced Bionics.

* cited by examiner

Primary Examiner — Rosemary K Tarcza

(74) *Attorney, Agent, or Firm* — Henricks, Slavin & Holmes
LLP

(57) **CLAIM**

The ornamental design for a single slot USB battery charger,
as shown and described.

DESCRIPTION

The present application is related to PCT patent application
Ser. No. PCT/US2011/047648, filed Aug. 12, 2011 and
entitled "Procedure Using Power From a Power Source Hav-
ing a USB Connector to Recharge a Battery for a Hearing
Device for the Hearing Impaired and a Battery Charger
Therefor," which is incorporated herein by reference in its
entirety.

FIG. 1 is a perspective view of a single slot USB battery
charger showing our new design;
FIG. 2 is a top view thereof;
FIG. 3 is a bottom view thereof;
FIG. 4 is a right side view thereof;
FIG. 5 is a front view thereof; and,
FIG. 6 is a rear view thereof.

1 Claim, 1 Drawing Sheet




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6

