



US00D689205S

(12) **United States Design Patent**
Guertin

(10) **Patent No.:** **US D689,205 S**

(45) **Date of Patent:** **** Sep. 3, 2013**

(54) **U-SHAPED TERMINATION PADDING**

(75) **Inventor:** **Chris Guertin**, Minneapolis, MN (US)

(73) **Assignee:** **Sport Resource Group, Inc.**,
Minneapolis, MN (US)

(**) **Term:** **14 Years**

(21) **Appl. No.:** **29/398,402**

(22) **Filed:** **Jul. 29, 2011**

(51) **LOC (9) Cl.** **25-01**

(52) **U.S. Cl.**
USPC **D25/121**

(58) **Field of Classification Search**
USPC D25/121; D21/333; 52/800.12,
52/800.15, 800.17, 716.1, 716.8, 717.01,
52/717.03, 579, 211, 465, 420, 417; 49/373,
49/490.1; 472/92, 94

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,600,946	A *	9/1926	Joiner	105/409
2,140,844	A *	12/1938	Mirus-Leuschner	49/490.1
2,281,185	A *	4/1942	Forster	52/797.1
2,443,676	A *	6/1948	Cosper	49/440
2,457,964	A *	1/1949	Wyche	52/800.12
2,718,678	A *	9/1955	Ramsay	49/490.1
2,793,406	A *	5/1957	Focht	49/490.1
3,374,578	A *	3/1968	Mesnel	49/440
3,416,282	A *	12/1968	Daugherty	52/716.8
3,430,394	A *	3/1969	Johnston	52/127.1
4,768,320	A *	9/1988	Weller	52/211
D324,575	S *	3/1992	Davis	D25/119
6,073,625	A *	6/2000	Ball	126/547
6,357,187	B1 *	3/2002	Haldeman	52/211
7,302,880	B1 *	12/2007	Elastic	89/36.07

2003/0032490	A1 *	2/2003	Martin et al.	472/92
2007/0119108	A1 *	5/2007	Downard	52/289
2011/0023372	A1 *	2/2011	Miyakawa et al.	49/490.1

OTHER PUBLICATIONS

Memorandum to NHL Arena Supply Manufacturers regarding implementation of curved glass, dated Jul. 20, 2011.

Memorandum to NHL General Managers and Arena Operations Personnel regarding implementation of curved glass, dated Jul. 20, 2011. "Specifications and Drawings for the Curved Corner System" prepared by ARCCA Incorporated for the NHL (National Hockey League), dated Jul. 2011.

* cited by examiner

Primary Examiner — Doris Clark

(74) *Attorney, Agent, or Firm* — Dorsey & Whitney LLP

(57) **CLAIM**

I claim the ornamental design for a u-shaped termination padding, as shown and described.

DESCRIPTION

FIG. 1 is a front isometric view of a u-shaped termination padding of the present invention, with the broken lines forming no part of the claimed design;

FIG. 2 is a front elevation view of the u-shaped termination padding of FIG. 1, with the broken lines forming no part of the claimed design;

FIG. 3 is a rear elevation view of the u-shaped termination padding of FIG. 1, with the broken lines forming no part of the claimed design;

FIG. 4 is a left elevation view of the u-shaped termination padding of FIG. 1, with the broken lines forming no part of the claimed design; and,

FIG. 5 is a top plan view of the u-shaped termination padding of FIG. 1, with the broken lines forming no part of the claimed design.

1 Claim, 4 Drawing Sheets






Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5