



US00D689488S

(12) **United States Design Patent**  
**Halsinger et al.**

(10) **Patent No.:** **US D689,488 S**

(45) **Date of Patent:** **\*\* Sep. 10, 2013**

(54) **CONTROL INTERFACE OF A COORDINATE INPUT DEVICE**

(75) Inventors: **Kai Halsinger**, Portland, OR (US);  
**Pierre Harper**, Santa Cruz, CA (US);  
**Samuel James Amis**, Portland, OR (US)

(73) Assignee: **Wacom Co., Ltd.**, Kazo-shi (JP)

(\*\*) Term: **14 Years**

(21) Appl. No.: **29/412,779**

(22) Filed: **Feb. 7, 2012**

(30) **Foreign Application Priority Data**

Aug. 8, 2011 (JP) ..... 2011-18156

(51) **LOC (9) Cl.** ..... **14-02**

(52) **U.S. Cl.**  
USPC ..... **D14/389**

(58) **Field of Classification Search**

USPC ..... D14/388-390, 341, 383, 374, 381,  
D14/371, 129, 456; D19/52; D10/65;  
178/18.01, 18.03-18.09, 18.11; 345/173-178;  
D1/127, 128, 199; D24/101-104; 424/467;  
D25/113, 119, 121-132; D21/499; D5/55-58,  
D5/62; 426/5, 87, 103, 264, 513, 660  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

D10,993 S \* 1/1879 Herter ..... D5/62  
232,140 A \* 9/1880 Mason ..... 273/157 R  
D46,714 S \* 12/1914 Brandt ..... D5/62

D90,348 S \* 7/1933 Susi ..... D5/62  
D202,498 S \* 10/1965 Lansky ..... D25/141  
3,979,532 A \* 9/1976 Muck et al. .... 427/245  
D327,577 S \* 7/1992 Nijhoff ..... D5/44  
D485,991 S \* 2/2004 Boehm et al. .... D5/7  
D561,352 S \* 2/2008 Stein ..... D25/103  
D600,012 S \* 9/2009 Ledbetter et al. .... D3/248  
D629,621 S \* 12/2010 Steeman et al. .... D5/58  
D652,960 S \* 1/2012 Canales et al. .... D25/138  
D661,105 S \* 6/2012 Gemperline ..... D5/55

\* cited by examiner

*Primary Examiner* — Cathron Brooks

*Assistant Examiner* — Katie Mroczka

(74) *Attorney, Agent, or Firm* — Christensen O'Connor  
Johnson Kindness PLLC


(57) **CLAIM**


The ornamental design for a control interface of a coordinate input device, as shown and described.

**DESCRIPTION**


FIG. 1 is a front elevation view of a control interface of a coordinate input device showing our new design;  
FIG. 2 is a rear elevation view of the coordinate input device shown in FIG. 1;  
FIG. 3 is a left side elevation view thereof;  
FIG. 4 is a right side elevation view thereof;  
FIG. 5 is a top plan view thereof;  
FIG. 6 is a bottom plan view thereof;  
FIG. 7 is a bottom front left isometric view of the control interface of the coordinate input device shown in FIG. 1; and, FIG. 8 is a closeup view of portion A-A of FIG. 7.  
The broken lines shown in FIGS. 1-8 illustrate environmental subject matter and form no part of the claimed design.

**1 Claim, 3 Drawing Sheets**






*Fig. 1.*




*Fig. 2.*




*Fig. 3.*



*Fig. 4.*



*Fig. 5.*



*Fig. 6.*

