



US00D689489S

(12) **United States Design Patent**  
**Halsinger et al.**

(10) **Patent No.:** **US D689,489 S**

(45) **Date of Patent:** **\*\* Sep. 10, 2013**

(54) **COORDINATE INPUT DEVICE**

(75) Inventors: **Kai Halsinger**, Portland, OR (US);  
**Pierre Harper**, Santa Cruz, CA (US);  
**Samuel James Amis**, Portland, OR (US)

(73) Assignee: **Wacom Co., Ltd.**, Kazo-shi (JP)

(\*\*) Term: **14 Years**

(21) Appl. No.: **29/412,783**

(22) Filed: **Feb. 7, 2012**

(30) **Foreign Application Priority Data**

Aug. 8, 2011 (JP) ..... 2011-18157

(51) **LOC (9) Cl.** ..... **14-02**

(52) **U.S. Cl.**  
USPC ..... **D14/389**

(58) **Field of Classification Search**  
USPC ..... D14/388-390, 383, 374, 381, 371,  
D14/129, 456, 138 AA-138 G, 341-346,  
D14/486; D19/52; D10/65; 178/18.01,  
178/18.03-18.09, 18.11; 345/173-178  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

D450,058 S \* 11/2001 Istvan et al. .... D14/486  
D495,715 S \* 9/2004 Gildred ..... D14/486  
D620,947 S \* 8/2010 Loken ..... D14/485  
D625,727 S 10/2010 Crisp  
D625,728 S 10/2010 Crisp

D629,401 S 12/2010 Crisp  
D629,402 S 12/2010 Crisp  
D629,418 S \* 12/2010 Brown et al. .... D14/486  
D630,224 S \* 1/2011 Allen ..... D14/485  
D635,148 S \* 3/2011 Loken ..... D14/486  
D637,605 S \* 5/2011 Brinda ..... D14/488  
D646,691 S \* 10/2011 Thai et al. .... D14/486  
D646,694 S \* 10/2011 Thai et al. .... D14/486  
D658,677 S \* 5/2012 Gleasman et al. .... D14/488  
D666,630 S \* 9/2012 LeVee et al. .... D14/486  
D679,284 S \* 4/2013 Rounding et al. .... D14/486  
2011/0069022 A1\* 3/2011 Yokota et al. .... 345/173

\* cited by examiner

*Primary Examiner* — Cathron Brooks

*Assistant Examiner* — Katie Mroczka

(74) *Attorney, Agent, or Firm* — Christensen O'Connor  
Johnson Kindness PLLC


(57) **CLAIM**


The ornamental design for a coordinate input device, as shown and described.

**DESCRIPTION**


FIG. 1 is a front elevation view of a coordinate input device showing our new design;  
FIG. 2 is a rear elevation view of the coordinate input device shown in FIG. 1;  
FIG. 3 is a left side elevation view thereof;  
FIG. 4 is a right side elevation view thereof;  
FIG. 5 is a top plan view thereof; and,  
FIG. 6 is a bottom plan view thereof.  
The broken lines shown in FIGS. 1-6 illustrate environmental subject matter and form no part of the claimed design.

**1 Claim, 2 Drawing Sheets**






*Fig. 1.*



*Fig. 2.*



*Fig.3.*



*Fig.4.*



*Fig.5.*



*Fig.6.*