



US00D689785S

(12) **United States Design Patent**
Miller et al.

(10) **Patent No.:** **US D689,785 S**

(45) **Date of Patent:** **** Sep. 17, 2013**

(54) **CONTROL FOR SIREN AND LIGHT BAR**

(75) Inventors: **Daniel S. Miller**, St. Louis, MO (US);
Roger L. Miller, Louisville, KY (US);
Daniel S. Pursley, St. Peters, MO (US);
John C. Davis, Eureka, MO (US)

(73) Assignee: **Code 3, Inc.**, St. Louis, MO (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/392,502**

(22) Filed: **May 23, 2011**

(51) **LOC (9) Cl.** **10-05**

(52) **U.S. Cl.**
USPC **D10/106.1**

(58) **Field of Classification Search**
USPC D10/106.1; D13/162
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D273,470 S 4/1984 Olson
D412,678 S * 8/1999 Smith et al. D10/106.1
6,646,548 B2 11/2003 Dornfeld

(Continued)

OTHER PUBLICATIONS

RLS Series Sirens and Controls, Installation & Operation Manual,
3990 Series Sirens (2006) 28 pages.

Primary Examiner — George D Kirschbaum

(74) *Attorney, Agent, or Firm* — Senniger Powers LLP

(57) **CLAIM**

The ornamental design for a control for siren and light bar, as shown and described.

DESCRIPTION

FIG. 1 illustrates a perspective of one embodiment of the control for siren and light bar of my new design;




FIG. 2 illustrates a front elevation of the control for siren and light bar of FIG. 1;

FIG. 2 also illustrates a top plan view of a screen shot of an embodiment of the control for siren and light bar as presented on a computer screen;

FIG. 3 illustrates a top plan of the control for siren and light bar of FIG. 1;

FIG. 4 illustrates a right side elevation of the control for siren and light bar of FIG. 1;

FIG. 5 illustrates a rear elevation of the control for siren and light bar of FIG. 1;

FIG. 6 illustrates a bottom plan of the control for siren and light bar of FIG. 1;

FIG. 7 illustrates a left side elevation view of the control for siren and light bar of FIG. 1;

FIG. 8 illustrates a perspective of another embodiment of the control for siren and light bar of my new design, lined for color;

FIG. 9 illustrates a front elevation of the control for siren and light bar of FIG. 8;

FIG. 10 illustrates a top plan of the control for siren and light bar of FIG. 8;

FIG. 10 also illustrates a top plan view of a screen shot of an embodiment of the control for siren and light bar as presented on a computer screen;

FIG. 11 illustrates a right side elevation of the control for siren and light bar of FIG. 8;


FIG. 12 illustrates a rear elevation of the control for siren and light bar of FIG. 8;

FIG. 13 illustrates a bottom plan of the control for siren and light bar of FIG. 8; and,

FIG. 14 illustrates a left side elevation view of the control for siren and light bar of FIG. 8.

In FIGS. 8-14, the toggle switch and the left section of the faceplate of the control for siren and light bar are lined for the color red, the center section of the faceplate of the control for siren and light bar is lined for blue, and the upper right section of the faceplate of the control for siren and light bar is lined for yellow (e.g., amber).

1 Claim, 14 Drawing Sheets



US D689,785 S

Page 2

(56)

References Cited

U.S. PATENT DOCUMENTS				D505,351 S	5/2005	Case et al.		
				D574,799 S	8/2008	Cronmiller et al.		
				D647,062 S *	10/2011	Deyaf	D13/162	
				2007/0016452 A1	1/2007	Wilson		
6,856,242 B2	2/2005	Trent						
D503,644 S *	4/2005	Case et al.	D10/106.1					* cited by examiner

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14

