



US00D690698S

(12) **United States Design Patent**
Jonsson et al.

(10) **Patent No.:** **US D690,698 S**
(45) **Date of Patent:** **** Oct. 1, 2013**

(54) **COORDINATE INPUT DEVICE**

(75) Inventors: **Carl Jonsson**, Portland, OR (US); **Jason Martin**, Lake Oswego, OR (US);
Patrick Triato, Portland, OR (US)

(73) Assignee: **Wacom Co., Ltd.**, Kazo-shi (JP)

(**) Term: **14 Years**

(21) Appl. No.: **29/424,426**

(22) Filed: **Jun. 12, 2012**

(30) **Foreign Application Priority Data**

Dec. 12, 2011 (JP) 2011-28827
Dec. 12, 2011 (JP) 2011-28828
Dec. 12, 2011 (JP) 2011-28829

(51) **LOC (9) Cl.** **14-02**

(52) **U.S. Cl.**
USPC **D14/390**

(58) **Field of Classification Search**

USPC D14/388–390, 341, 383, 374, 381,
D14/371, 129, 456; D19/52; D10/65;
178/18.01, 18.03–18.09, 18.11; 345/173–178
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D505,676 S * 5/2005 Porter et al. D14/388
D554,640 S * 11/2007 Ponnert et al. D14/388

(Continued)

FOREIGN PATENT DOCUMENTS

JP D1372958 S 11/2009
JP D1372960 S 11/2009
JP D1372961 S 11/2009
JP D1372962 S 11/2009

OTHER PUBLICATIONS

“Virtuoso T5000 (Kanvus Virtuoso T5000),” Product Information,
Kanvus, Jhonghe City, Taiwan, <<http://www.kanvus-global.com/>>

main/prod_in.aspx?mnuid=1524&modid=26&prodid=454
&flag=1> [retrieved Feb. 13, 2013].

Primary Examiner — Barbara Fox

Assistant Examiner — Katie Mroczka

(74) *Attorney, Agent, or Firm* — Christensen O’Connor
Johnson Kindness PLLC

(57) **CLAIM**

The ornamental design for a coordinate input device, as
shown and described.

DESCRIPTION

FIG. 1 is a front elevation view of a coordinate input device
showing our new design;

FIG. 2 is a rear elevation view thereof;

FIG. 3 is a left side elevation view thereof;

FIG. 4 is a right side elevation view thereof;

FIG. 5 is a top plan view thereof, wherein the bottom plan
view is the same as the top plan view;

FIG. 6 is a top front left isometric view thereof;

FIG. 7 is a close up view of a portion defined by A-A and B-B
of FIG. 6;

FIG. 8 is a front elevation view of a coordinate input device
showing a variant of the design;

FIG. 9 is a rear elevation view thereof;

FIG. 10 is a left side elevation view thereof;

FIG. 11 is a right side elevation view thereof;



FIG. 12 is a top plan view thereof, wherein the bottom plan
view is the same as the top plan view;

FIG. 13 is a top front left isometric view thereof; and,

FIG. 14 is a close up view of a portion defined by A-A and B-B
of FIG. 13.

The broken lines shown in the figures that are immediately
adjacent to the shaded areas and define unshaded regions,
represent the bounds of the claim; the broken lines form no
part of the claimed design.

1 Claim, 10 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

D587,267 S * 2/2009 Wang D14/356

D590,018 S * 4/2009 Nash et al. D19/52

D596,173 S * 7/2009 Arfin D14/307

D602,014 S * 10/2009 Andre et al. D14/341

D624,914 S * 10/2010 Wang D14/371

D629,400 S 12/2010 Harper

D629,402 S * 12/2010 Crisp et al. D14/390

D631,047 S * 1/2011 Hirota D14/390

D634,319 S * 3/2011 Andre et al. D14/341

D648,723 S 11/2011 Harper

D662,094 S * 6/2012 Mack et al. D14/388

D667,395 S * 9/2012 Lee D14/341

D671,117 S * 11/2012 Harper et al. D14/371

D671,940 S * 12/2012 Kim D14/374

D672,345 S * 12/2012 Li D14/341

D673,561 S * 1/2013 Hyun et al. D14/341

D679,274 S * 4/2013 Canizares et al. D14/341

2012/0105375 A1 * 5/2012 Yamada 345/175

2012/0218206 A1 * 8/2012 Sato et al. 345/173

2013/0082937 A1 * 4/2013 Liu et al. 345/173

2013/0082979 A1 * 4/2013 Rabu et al. 345/175

* cited by examiner




Fig. 1.




Fig. 2.




Fig. 3.



Fig. 4.




Fig. 5.




Fig.6.




Fig. 7.




Fig. 8.




Fig. 9.




Fig. 10.




Fig. 11.




Fig. 12.




Fig. 13.




Fig. 14.