

#### (12) United States Design Patent US D690,909 S (10) Patent No.: Oct. 8, 2013 Albers (45) **Date of Patent:** \*\*

#### **BIB WITH POUCH** (54)

- **Oliver Albers**, Oakland, CA (US) (75)Inventor:
- Assignee: Luft Industrie Inc., Oakland, CA (US) (73)

(\*\*)14 Years Term:

Appl. No.: 29/408,662 (21)

			Bland D2/864
D644,005	S *	8/2011	Davis D2/864
			Hansen et al D2/864
2007/0143904	A1*	6/2007	Brown 2/49.1
2007/0157357	A1*	7/2007	Cymbol 2/49.2
2009/0188016	A1*	7/2009	Arthur-Mensah et al 2/49.4

### \* cited by examiner

Primary Examiner — Rashida Johnson (74) Attorney, Agent, or Firm — Onello & Mello, LLP

(22)	Filed:	Dec. 15, 2011	
(51)	LOC (9)	<b>Cl.</b>	
(52)	U.S. Cl.		
	USPC		D2/864
(58)	Field of (	<b>Classification Search</b>	

USPC ...... D2/860–864; 2/46, 48–49.2, 50–52 See application file for complete search history.

### **References** Cited (56)

### U.S. PATENT DOCUMENTS

D310,148	S	*	8/1990	Cleary et al D6/600
D350,220	S	*	9/1994	Lindy D2/864
D394,339	S	*	5/1998	Hill D2/864
6,237,150	B1	*	5/2001	Lucas 2/49.1
6,481,016	B1	*	11/2002	Rees 2/49.1
D526,765	S	*	8/2006	Lown et al D2/860
D541,012	S	*	4/2007	Gottehrer D2/864

CLAIM

(57)An ornamental design for a bib with pouch, as shown and described.

### DESCRIPTION

FIG. 1 is a front view of a bib with pouch with the pouch in a closed position, in accordance with the present invention; FIG. 2 is a rear view of the bib with pouch of FIG. 1 with the pouch in the closed position; FIG. 3 is a side perspective view of the bib with pouch of FIG. 1 with the pouch in the closed position; FIG. 4 is a front view of the bib with pouch of FIG. 1 with the pouch in an opened position; and, FIG. 5 is a rear view of the bib with pouch of FIG. 1 with the pouch in the opened position.

### 1 Claim, 5 Drawing Sheets



# U.S. Patent Oct. 8, 2013 Sheet 1 of 5 US D690,909 S



FIG. 1

# U.S. Patent Oct. 8, 2013 Sheet 2 of 5 US D690,909 S



FIG. 2

# U.S. Patent Oct. 8, 2013 Sheet 3 of 5 US D690,909 S



## U.S. Patent Oct. 8, 2013 Sheet 4 of 5 US D690,909 S

-



FIG. 4

# U.S. Patent Oct. 8, 2013 Sheet 5 of 5 US D690,909 S



FIG. 5