



US00D692371S

(12) **United States Design Patent**
Fontaine et al.

(10) **Patent No.:** **US D692,371 S**
(45) **Date of Patent:** **** Oct. 29, 2013**

(54) **TIRE**

(75) Inventors: **Sebastien Willy Fontaine**, Vichten
(LU); **Pierre Bernard Raoul Brochet**,
Itzig (LU); **Nigel Carl Hosker**,
Grevenknapp (LU)

(73) Assignee: **The Goodyear Tire & Rubber
Company**, Akron, OH (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/414,620**

(22) Filed: **Mar. 1, 2012**

(51) **LOC (9) Cl.** **12-15**

(52) **U.S. Cl.**
USPC **D12/517**

(58) **Field of Classification Search**
USPC D12/505–532, 900–901;
152/209.1–209.9, 209.11–209.19,
152/209.21–209.28, 455
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D334,360 S	3/1993	Graas et al.	D12/146
D423,422 S	4/2000	Selover et al.	D12/146
D432,956 S	10/2000	Ricquet	D12/141
D451,440 S	12/2001	Weber	D12/146
D451,441 S	12/2001	Weber	D12/146
D453,729 S	2/2002	Demagall et al.	D12/523
D470,101 S	2/2003	Heinen	D12/584
D482,323 S	11/2003	Corbin et al.	D12/584
D490,045 S	5/2004	Delu et al.	D12/519
D558,126 S	12/2007	Shavers et al.	D12/519
D558,127 S	12/2007	Shavers et al.	D12/519
D559,168 S	1/2008	Murata	D12/523
D559,767 S	1/2008	Graas et al.	D12/521
D584,213 S	1/2009	Shinkai	D12/519
D586,723 S *	2/2009	Heinen et al.	D12/517
D586,726 S	2/2009	Baumard et al.	D12/521
D599,276 S	9/2009	Fontaine et al.	D12/519
D600,193 S	9/2009	Nukala et al.	D12/521

D601,939 S	10/2009	Fontaine et al.	D12/519
D609,161 S	2/2010	Fontaine et al.	D12/517
D624,870 S *	10/2010	Fontaine et al.	D12/517
D633,433 S	3/2011	Sieber et al.	D12/519
D634,699 S	3/2011	Fontaine et al.	D12/517
D635,911 S	4/2011	Sieber et al.	D12/521
D644,593 S	9/2011	Fontaine et al.	D12/523
D661,242 S *	6/2012	Schmidt-Zum Berge et al.	D12/517
D667,775 S *	9/2012	Rittweger	D12/515
D668,202 S *	10/2012	Bonnamour et al.	D12/517
D675,148 S *	1/2013	Kiwaki	D12/517

* cited by examiner

Primary Examiner — Stacia Cadmus

(74) *Attorney, Agent, or Firm* — Richard B. O'Planick

(57) **CLAIM**

The ornamental design for a tire, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a tire showing our new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread;

FIG. 2 is a front elevational view thereof;

FIG. 3 is a right side elevational view thereof;

FIG. 4 is a left side elevational view thereof;



FIG. 5 is an enlarged fragmentary front elevational view thereof;

FIG. 6 is a perspective view of a second embodiment of a tire showing our new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread; and,

FIG. 7 is a front elevational view of a second embodiment, it being understood that an enlarged fragmentary view thereof would be substantially identical to that shown in FIG. 5, with the exception of the inclusion of the sidewall in solid lines.

In the drawings, the broken lines showing of the sidewall, inner bead and the peripheral boundary between the tire tread and the sidewall in FIGS. 1 through 5 depict environmental subject matter and form no part of the claimed design.

1 Claim, 7 Drawing Sheets






FIG-1




FIG-2




FIG-3




FIG-4




FIG-5




FIG-6




FIG-7