

US00D692954S

(12) **United States Design Patent**  
**Eisenberg et al.**

(10) **Patent No.:** **US D692,954 S**

(45) **Date of Patent:** **\*\* Nov. 5, 2013**

(54) **DOOR HANGER WITH COLLAR STAY CARD**

2008/0134410 A1\* 6/2008 Eisenberg ..... 2/132

\* cited by examiner

(76) Inventors: **Jordan D. Eisenberg**, Denver, CO (US);  
**Randall S. Kaplan**, Los Angeles, CA  
(US)

*Primary Examiner* — Mary Ann Calabrese  
(74) *Attorney, Agent, or Firm* — Holland & Hart LLP

(\*\*) Term: **14 Years**

(57) **CLAIM**

The ornamental design for a door hanger with collar stay card,  
as shown and described.

(21) Appl. No.: **29/425,788**

**DESCRIPTION**

(22) Filed: **Jun. 27, 2012**

(51) **LOC (9) Cl.** ..... **20-02**

(52) **U.S. Cl.**

USPC ..... **D20/42**; D20/40; D20/19

(58) **Field of Classification Search**

USPC ..... D20/10, 19, 22, 23, 27, 29, 40, 42, 99;  
40/1, 124.01–124.09, 124.11–124.19,  
40/124.191, 299.01, 446, 538, 584, 617;  
D2/602, 609, 859; D8/402; D19/1, 9,  
D19/10; 2/132; 283/56, 71, 91

See application file for complete search history.



FIG. 1 is a front perspective view of the door hanger with collar stay card, showing our new design;  
FIG. 2 is a left side elevation view of the design illustrated in FIG. 1;  
FIG. 3 is a front view of the design illustrated in FIG. 1;  
FIG. 4 is a right side elevation view of the design illustrated in FIG. 1;  
FIG. 5 is a top view of the design illustrated in FIG. 1;  
FIG. 6 is a bottom view of the design illustrated in FIG. 1;  
FIG. 7 is a rear view of the design illustrated in FIG. 1;  
FIG. 8 is a front perspective view of the door hanger with collar stay card, showing another embodiment of our new design;  
FIG. 9 is a left side elevation view of the design illustrated in FIG. 8;  
FIG. 10 is a front view of the design illustrated in FIG. 8;  
FIG. 11 is a right side elevation view of the design illustrated in FIG. 8;  
FIG. 12 is a top view of the design illustrated in FIG. 8;  
FIG. 13 is a bottom view of the design illustrated in FIG. 8;  
and,  
FIG. 14 is a rear view of the design illustrated in FIG. 8.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

|           |     |         |                  |       |        |
|-----------|-----|---------|------------------|-------|--------|
| 4,462,175 | A * | 7/1984  | Romberger        | ..... | 40/1   |
| D429,286  | S * | 8/2000  | Luciani et al.   | ..... | D20/42 |
| D456,703  | S * | 5/2002  | Sornsriwichai    | ..... | D8/402 |
| D476,694  | S * | 7/2003  | Snow             | ..... | D20/27 |
| D477,368  | S * | 7/2003  | Massey           | ..... | D20/27 |
| D540,392  | S * | 4/2007  | Taylor           | ..... | D20/40 |
| D616,293  | S * | 5/2010  | Goodman et al.   | ..... | D8/402 |
| D649,200  | S * | 11/2011 | Whittier et al.  | ..... | D20/43 |
| D666,790  | S * | 9/2012  | Eisenberg et al. | ..... | D2/859 |
| D678,661  | S * | 3/2013  | Eisenberg et al. | ..... | D2/859 |

**1 Claim, 6 Drawing Sheets**






FIG.1

---

FIG.5




FIG.2

FIG.3

FIG.4

---

FIG.6




FIG.7




FIG.8

---

FIG.12




FIG.9

FIG.10

FIG.11

---

FIG.13




FIG.14