



US00D697439S

(12) **United States Design Patent**
Moeller

(10) **Patent No.:** **US D697,439 S**
(45) **Date of Patent:** **** Jan. 14, 2014**

(54) **SENSOR**

(71) Applicant: **Steinel GmbH**, Herzebrock (DE)

(72) Inventor: **Thomas Moeller**, Herford (DE)

(73) Assignee: **Steinel GmbH**, Herzebrock (DE)

(**) Term: **14 Years**

(21) Appl. No.: **29/436,442**

(22) Filed: **Nov. 6, 2012**

(30) **Foreign Application Priority Data**

May 8, 2012 (EM) 002038380-0001

May 8, 2012 (EM) 002038380-0002

(51) **LOC (10) Cl.** **10-04**

(52) **U.S. Cl.**

USPC **D10/70; D10/106.6**

(58) **Field of Classification Search**

USPC D10/65, 70, 75, 78, 104.1,
D10/106.1-106.8; D14/138 R, 138 AA,
D14/138 AB, 138 AC, 138 AD, 341-347,
D14/507-510, 136, 167, 168, 496, 498, 499,
D14/500, 125-134, 239, 371, 374-377, 440,
D14/450, 448, 336, 342; 343/702; 345/87,
345/104, 133, 156, 168, 173, 901-905,
345/165; 348/180, 184, 315, 739, 836, 838,
348/325; 364/444, 499; 701/408-418, 431,
701/432, 537; 312/7.2; 341/12; 720/605,
720/669, 600, 655; 369/99, 197; 455/344,
455/347, 575.1; 250/221, 338.3, 340, 239,
250/342, 341, DIG. 1, 353; 307/116, 117;

340/521, 527, 541, 567, 540, 568.2,
340/539.23, 635, 687; 315/159; 324/72.5,
324/556, 133, 149, 503, 543, 555, 66, 72,
324/754, 115, 141, 522; 73/615, 624, 627,
73/644, 514.33, 514.34, 510, 513, 527,
73/530; 356/3.01-5.15; 235/105; 377/5,
377/24.2, 26; 702/155, 160, 176, 78, 79,
702/82, 91-95, 104, 116, 141, 150, 151,
702/154, 127, 131, 182, 183, 189; 600/437,
600/443, 453, 459, 465, 479, 500, 502, 595,
600/485, 481, 483

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D591,628 S * 5/2009 Tsurumi D10/106.5

D591,629 S * 5/2009 Tsurumi D10/106.5

D591,630 S * 5/2009 Tsurumi D10/106.5

D664,876 S * 8/2012 Krumpel et al. D10/106.6

* cited by examiner

Primary Examiner — Antoine D Davis

(74) *Attorney, Agent, or Firm* — Bachman & LaPointe, P.C.

(57) **CLAIM**

The ornamental design of a sensor, as shown.

DESCRIPTION

FIG. 1 is a front view showing the ornamental design of a sensor in accordance with the present invention; and, FIG. 2 is a side view of the sensor of FIG. 1.

1 Claim, 2 Drawing Sheets






FIG. 1




FIG. 2