



US00D700042S

(12) **United States Design Patent**
Cobianco

(10) **Patent No.:** **US D700,042 S**
(45) **Date of Patent:** **** Feb. 25, 2014**

- (54) **DOUBLE-SIDED HOOK**
- (71) Applicant: **Roger L Cobianco**, Spring Hill, FL (US)
- (72) Inventor: **Roger L Cobianco**, Spring Hill, FL (US)
- (**) Term: **14 Years**
- (21) Appl. No.: **29/432,501**
- (22) Filed: **Sep. 16, 2012**
- (51) **LOC (10) Cl.** **08-01**
- (52) **U.S. Cl.**
USPC **D8/367**
- (58) **Field of Classification Search**
USPC D8/367; 248/301-304, 215
See application file for complete search history.

6,012,204 A	1/2000	Roethler	
D469,682 S *	2/2003	Gary et al.	D8/367
D475,278 S *	6/2003	Williams	D8/367
D493,092 S *	7/2004	Kalat	D8/367
6,851,163 B2	2/2005	Selby	
D560,924 S *	2/2008	Walker	D6/396
7,908,716 B2	3/2011	Soresen	
D644,438 S *	9/2011	Brucker	D3/328

* cited by examiner

Primary Examiner — Holly Baynham
(74) *Attorney, Agent, or Firm* — Law Office of Steven R. Olsen, PLLC; Steven R. Olsen

(57) **CLAIM**
The ornamental design for a double-sided hook, as shown and described.


(56) **References Cited**
U.S. PATENT DOCUMENTS

107,952 A	10/1870	Osborn	
242,655 A	6/1881	Kilmer	
402,786 A	5/1889	Tyler	
521,847 A	6/1894	Christensen	
904,747 A	11/1908	Anderson	
2,296,082 A	9/1942	Bierk	
2,642,640 A	6/1953	Mills	
D176,759 S *	1/1956	Frank	D8/367
4,432,121 A	2/1984	Dupre	
4,622,724 A	11/1986	Dupre	
4,998,495 A	3/1991	Bos et al.	
5,195,216 A	3/1993	Ishii	
5,339,498 A	8/1994	Parsons	
D368,219 S *	3/1996	Protz, Jr.	D8/371
5,575,446 A *	11/1996	Swenson et al.	248/304
5,625,925 A	5/1997	Richards	
5,630,257 A	5/1997	Brody et al.	
5,682,652 A	11/1997	Brody et al.	
5,964,698 A	10/1999	Fowler	

DESCRIPTION

FIG. 1 is a top view of my new design for a double-sided hook according to a first embodiment, a bottom view of the first embodiment being a mirror image thereof;
FIG. 2 is a first end view of the first embodiment;
FIG. 3 is a second end view of the first embodiment;
FIG. 4 is a first side view of the first embodiment;
FIG. 5 is a second side view of the first embodiment;
FIG. 6 is a top view of my new design for a double-sided hook according to a second embodiment, a bottom view of the second embodiment being a mirror image thereof;
FIG. 7 is a first end view of the second embodiment;
FIG. 8 is a second end view of the second embodiment;
FIG. 9 is a first side view of the second embodiment;
FIG. 10 is a second side view of the second embodiment; and,
FIG. 11 is a perspective view of the second embodiment.

1 Claim, 3 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3



FIG. 4




FIG. 5




FIG. 6



FIG. 7




FIG. 8



FIG. 9




FIG. 10




FIG. 11