

US00D702180S

(12) **United States Design Patent**
Le et al.

(10) **Patent No.:** **US D702,180 S**
(45) **Date of Patent:** **** Apr. 8, 2014**

(54) **TIRE**

(71) Applicant: **The Goodyear Tire & Rubber Company, Akron, OH (US)**

(72) Inventors: **Phuoc Thuan Le, Attert (BE); Herve Marcel Henri Beauguitte, Lieler (LU); Gerard Yvon Roland Weber, Rambrouch (LU); Alfred Gessner, Nudlingen-Haard (DE); Bernard Krack, Reimberg (LU)**

(73) Assignee: **The Goodyear Tire & Rubber Company, Akron, OH (US)**

(**) Term: **14 Years**

(21) Appl. No.: **29/444,542**

(22) Filed: **Jan. 31, 2013**

(51) **LOC (10) Cl.** **12-15**

(52) **U.S. Cl.**
USPC **D12/588**

(58) **Field of Classification Search**
USPC D12/568–603, 553, 900–901;
152/209.1–209.9, 209.11–209.19,
152/209.21–209.28, 455
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D369,134 S	*	4/1996	Koenigstein		D12/588
D383,712 S		9/1997	Scheuren et al.		D12/143
D384,613 S		10/1997	Le et al.		D12/146
D392,605 S		3/1998	Le et al.		D12/146
D403,281 S		12/1998	Allen et al.		D12/147
D426,178 S	*	6/2000	Weber et al.		D12/588
D448,709 S		10/2001	Le		D12/147
D458,215 S		6/2002	Le		D12/600
D461,162 S		8/2002	Youn et al.		D12/595
D464,614 S	*	10/2002	Irimiya		D12/588
D473,843 S		4/2003	Le et al.		D12/600
D500,288 S		12/2004	Maziarka et al.		D12/601
D502,444 S	*	3/2005	Wage		D12/588

D528,500 S		9/2006	Le et al.		D12/600
D533,498 S		12/2006	Scheuren et al.		D12/588
D554,055 S		10/2007	Beauguitte et al.		D12/600
D583,308 S	*	12/2008	Ludwig et al.		D12/588
D584,217 S		1/2009	Scheuren et al.		D12/549
D591,224 S	*	4/2009	Ludwig et al.		D12/588
D604,228 S		11/2009	Le et al.		D12/582
D604,229 S		11/2009	Le et al.		D12/582
D609,169 S		2/2010	Feider		D12/588
D619,081 S		7/2010	Nicolas et al.		D12/571
D626,501 S		11/2010	Cazin-Bourguignon et al.		D12/600
D627,707 S		11/2010	Le et al.		D12/566

(Continued)

Primary Examiner — Stacia Cadmus

(74) *Attorney, Agent, or Firm* — Richard B. O'Planick

(57) **CLAIM**

The ornamental design for a tire, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a tire showing our new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread;

FIG. 2 is a front elevational view thereof;

FIG. 3 is a right side elevational view thereof; the opposite side elevational view being identical thereto;



FIG. 4 is an enlarged fragmentary front elevational view thereof;

FIG. 5 is a perspective view of a second embodiment of a tire showing our new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread and that the opposite side view is identical thereto; and,

FIG. 6 is a front elevational view of a second embodiment, it being understood that an enlarged fragmentary view thereof would be substantially identical to that shown in FIG. 4, with the exception of the inclusion of the sidewall in solid lines.

In the drawings, the broken lines showing of the sidewall, inner bead and the peripheral boundary between the tire tread and the sidewall in FIGS. 1 through 4 depict environmental subject matter and form no part of the claimed design.

1 Claim, 6 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

D628,955 S12/2010Toumni et al.D12/588

D642,974 S*8/2011KoshioD12/600

D645,810 S9/2011Le et al.D12/600

D647,040 S10/2011Mathonet et al.D12/588

D648,264 S11/2011Le et al.D12/588

D657,302 S*4/2012DurandD12/590

D661,640 S6/2012KrierD12/588

D662,456 S*6/2012Corsi et al.D12/588

D667,781 S*9/2012Georges et al.D12/588

D668,601 S*10/2012Brown et al.D12/588

D674,741 S*1/2013Mathonet et al.D12/588

D686,973 S*7/2013OtaniD12/588

* cited by examiner




FIG-1




FIG-2




FIG-3




FIG-4




FIG-5




FIG-6