



US00D702409S

(12) **United States Design Patent**
Machács

(10) **Patent No.:** **US D702,409 S**
(45) **Date of Patent:** **** Apr. 8, 2014**

(54) **DRYING TOOL**

(71) Applicant: **Márton Machács**, Budapest (HU)

(72) Inventor: **Márton Machács**, Budapest (HU)

(**) Term: **14 Years**

(21) Appl. No.: **29/454,015**

(22) Filed: **May 6, 2013**

Related U.S. Application Data

(62) Division of application No. 29/402,131, filed on Sep. 21, 2011.

(30) **Foreign Application Priority Data**

Aug. 4, 2011 (EM) 0019007620001

Aug. 4, 2011 (EM) 0019007620002

Aug. 4, 2011 (EM) 0019007620003

Aug. 4, 2011 (EM) 0019007620004

(51) **LOC (10) Cl.** **07-05**

(52) **U.S. Cl.**
USPC **D32/60**

(58) **Field of Classification Search**

USPC D32/60, 35; D4/199; D6/328, 513;
D8/356, 377, 382; 15/256.6;
211/119.01, 119.1, 119.11, 119.12,
211/119.13, 119.18; 248/58; 223/85, 88,
223/98; 254/389; 385/136, 137; 403/209;
606/151

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,229,071 A * 1/1941 Godstrey 15/256.6
2,255,154 A * 9/1941 Esposito 15/256.6

(Continued)

Primary Examiner — Caaron D Veynar

Assistant Examiner — Martie K Holtje

(74) *Attorney, Agent, or Firm* — Stein IP, LLC

(57) **CLAIM**

The ornamental design for a drying tool, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of an embodiment of Applicant's drying tool composed of two symmetrical, semi-circular segments, joined together to form a cylindrical tool;

FIG. 2 is an end view of the cylindrical drying tool of FIG. 1, such view being taken along line 2-2 in FIG. 1;

FIG. 3 is a perspective view of the exterior face of one of the semi-cylindrical segments of the cylindrical drying tool of FIG. 1;

FIG. 4 is a perspective view of the interior face of one of the semi-cylindrical segments of the drying tool of FIG. 2;

FIG. 5 is a perspective view of the exterior face of the other semi-cylindrical segment of the drying tool of FIG. 1;

FIG. 6 is a perspective view of the semi-cylindrical segment of FIG. 4, showing the projections that fit into the bores on the opposing semi-cylindrical segment;

FIG. 7 is a perspective view of an alternative embodiment of applicant's drying tool, composed of two symmetrical semi-cylindrical segments joined together to form a cylindrical drying tool;

FIG. 8 is an end view of the alternative embodiment of FIG. 7, such view being taken along line 8-8 in FIG. 7;


FIG. 9 is a perspective view of the exterior face of one of the semi-cylindrical segments of the drying tool of FIG. 7;

FIG. 10 is a perspective view of the interior face of one of the semi-cylindrical segments of FIG. 7;

FIG. 11 is a perspective view of the exterior face of the other semi-cylindrical segments of the drying tool of FIG. 7; and,

FIG. 12 is a perspective view of the interior face of the other semi-cylindrical segment of FIG. 7 showing the protrusions that fit into the bores in the interior face of the opposing segment of FIG. 10.

1 Claim, 6 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

D204,889 S * 5/1966 Gingher D8/377

4,049,357 A * 9/1977 Hamisch, Jr. 403/209

4,845,877 A * 7/1989 Koetje 43/7

5,513,295 A * 4/1996 Go 385/137

D376,061 S * 12/1996 Aulenbach D6/513

5,966,902 A * 10/1999 Korycki 53/397

6,758,351 B1 * 7/2004 Klingsdal 211/119.18

D505,020 S * 5/2005 Fischer D6/328

D524,558 S * 7/2006 Fischer D6/328

D568,723 S * 5/2008 Morgan D8/356

D598,658 S * 8/2009 Peppard D4/199

D648,499 S * 11/2011 Machacs D32/60

D658,838 S * 5/2012 Machacs D32/60

2003/0136806 A1 * 7/2003 Mainetti 223/85

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12