



US00D707625S

(12) **United States Design Patent**
Ibuki et al.

(10) **Patent No.:** **US D707,625 S**
(45) **Date of Patent:** **** Jun. 24, 2014**

(54) **BATTERY CHARGER STAND FOR ELECTRONIC EQUIPMENT**

(71) Applicant: **Nintendo Co., Ltd.**, Kyoto (JP)

(72) Inventors: **Masato Ibuki**, Kyoto (JP); **Daisuke Kumazaki**, Kyoto (JP); **Masahiko Nishimura**, Kyoto (JP); **Hironori Furuike**, Kyoto (JP)

(73) Assignee: **Nintendo Co., Ltd.**, Kyoto (JP)

(**) Term: **14 Years**

(21) Appl. No.: **29/472,625**

(22) Filed: **Nov. 14, 2013**

(30) **Foreign Application Priority Data**

May 29, 2013 (JP) 2013-011875

(51) **LOC (10) Cl.** **13-02**

(52) **U.S. Cl.**
USPC **D13/108**

(58) **Field of Classification Search**

CPC Y02E 60/12; Y02T 90/14; Y02T 90/122; Y02T 90/128; Y02T 90/163; H02J 7/025; H02J 7/0042; H02J 7/0044; H02J 7/0045; H02J 7/0003; H01F 38/14; H01R 13/6675; H01M 2/1022; H01M 2/1055; H01M 10/44; H01M 10/46; H01M 10/425; B60L 11/182
USPC D13/107-110, 118-119, 184, 199; D14/251, 253, 432, 434; 320/107-115
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D199,728 S * 12/1964 Hall D4/199
D308,267 S * 5/1990 Bradd D32/31

D351,133 S * 10/1994 Jungels-Butler et al. D13/108
D361,978 S 9/1995 Shirai et al.
D454,837 S 3/2002 Ibuki et al.
D461,814 S * 8/2002 Felix et al. D14/434
D515,029 S * 2/2006 Hattori D13/108
D563,867 S * 3/2008 Ahlgren D13/107
D575,350 S * 8/2008 Ashida et al. D21/333
D609,637 S * 2/2010 Chu et al. D13/108
D609,638 S * 2/2010 Biheller et al. D13/108
D638,831 S * 5/2011 Paradise D14/253
D669,461 S * 10/2012 Wikel D14/253

OTHER PUBLICATIONS

Design U.S. Appl. No. 29/472,607, filed Nov. 14, 2013.

* cited by examiner

Primary Examiner — Rosemary K Tarcza

(74) *Attorney, Agent, or Firm* — Nixon & Vanderhye PC

(57) **CLAIM**

The ornamental designs for portions of a battery charger stand for electronic equipment, as shown by solid lines and described.

DESCRIPTION

FIG. 1 is a front, bottom and right perspective view of a battery charger stand for electronic equipment of our new design;

FIG. 2 is a rear, top and left perspective view thereof;

FIG. 3 is a front view thereof;

FIG. 4 is a rear view thereof;

FIG. 5 is a top plan view thereof;

FIG. 6 is a bottom plan view thereof;

FIG. 7 is a left side view thereof;

FIG. 8 is a right side view thereof; and,

FIG. 9 is a sectional view taken along line 9-9 in FIG. 3.

1 Claim, 3 Drawing Sheets




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9

