



US00D707936S

(12) **United States Design Patent**
Nash et al.

(10) **Patent No.:** **US D707,936 S**

(45) **Date of Patent:** **** Jul. 1, 2014**

(54) **STABILIZING MEMBER FOR AN INSOLE**

(76) Inventors: **Rachael Nash**, Spearwood (AU);
Marie-Ann Ishak, Kinross (AU)

(**) Term: **14 Years**

(21) Appl. No.: **29/424,216**

(22) Filed: **Jun. 8, 2012**

(30) **Foreign Application Priority Data**

Dec. 9, 2011 (AU) 15676/2011

(51) **LOC (10) Cl.** **02-04**

(52) **U.S. Cl.**
USPC **D2/961**

(58) **Field of Classification Search**

CPC A43B 5/00; A43B 7/14; A43B 7/1405;
A43B 7/141; A43B 7/1415; A43B 7/142;
A43B 7/1425; A43B 7/143; A43B 7/1435;
A43B 7/144; A43B 7/1445; A43B 7/145;
A43B 7/1455; A43B 7/146; A43B 7/1465;
A43B 7/1475; A43B 7/148; A43B 7/1485;
A43B 7/149; A43B 7/22; A43B 7/28; A43B
13/38; A43B 13/39; A43B 13/383; A43B
13/386; A43B 13/40; A43B 13/00; A43B
13/02; A43B 13/04; A43B 21/32; A43B
5/0405; A43B 5/0407

USPC D2/896, 946, 947, 949, 950, 954, 961,
D2/968; 36/83, 88, 91, 92, 93, 25 R, 28, 29,
36/32 R, 30 R, 43, 44, 71

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,644,250	A *	7/1953	Ciaio	36/76 R
4,231,169	A *	11/1980	Toyama et al.	36/43
4,266,350	A *	5/1981	Laux	36/44
4,338,734	A *	7/1982	Schwartz	36/44
4,353,173	A *	10/1982	Paquet	36/44
D322,508	S *	12/1991	Riecken	D2/961
D328,967	S *	9/1992	Brown	D2/961
D332,003	S *	12/1992	Brown	D2/961
D414,024	S *	9/1999	Kress et al.	D2/961
D533,336	S *	12/2006	Walker	D2/961
7,941,938	B2 *	5/2011	Yu et al.	36/25 R
D642,363	S *	8/2011	Rajmohan et al.	D2/961
8,479,413	B2 *	7/2013	Avent et al.	36/44
D695,000	S *	12/2013	Feldman	D2/961
D695,506	S *	12/2013	Faux et al.	D2/961
D696,506	S *	12/2013	Feldman	D2/961

* cited by examiner

Primary Examiner — Elizabeth J Oswecki

(74) *Attorney, Agent, or Firm* — McAndrews, Held & Malloy, Ltd.



(57) **CLAIM**

The ornamental design for a stabilizing member for an insole, as shown and described.

DESCRIPTION

FIG. 1 is a left side, perspective view of a stabilizing member for an insole showing our new design;
FIG. 2 is a right side, perspective view thereof;
FIG. 3 is a bottom perspective view thereof;
FIG. 4 is a right side, bottom perspective view thereof;
FIG. 5 is a left side, bottom perspective view thereof;
FIG. 6 is a right side view thereof;
FIG. 7 is a left side view thereof; and,
FIG. 8 is a bottom plan view thereof.

1 Claim, 2 Drawing Sheets






FIG. 2




FIG. 1



FIG. 3




FIG. 4




FIG. 5



FIG. 6




FIG. 7



FIG. 8