



US00D709102S

(12) **United States Design Patent**  
**Tokuda et al.**

(10) **Patent No.:** **US D709,102 S**  
(45) **Date of Patent:** **\*\* Jul. 15, 2014**

(54) **PORTION OF OPERATION GRIP FOR MACHINE**

(71) Applicant: **Kubota Corporation**, Osaka (JP)

(72) Inventors: **Takayuki Tokuda**, Sakai (JP);  
**Masahiro Yamamoto**, Osaka (JP);  
**Toshiaki Otani**, Sakai (JP)

(73) Assignee: **Kubota Corporation**, Osaka (JP)

(\*\*) Term: **14 Years**

(21) Appl. No.: **29/468,471**

(22) Filed: **Sep. 30, 2013**

(30) **Foreign Application Priority Data**

Jul. 22, 2013 (JP) ..... 2013-016570

(51) **LOC (10) Cl.** ..... **15-03**

(52) **U.S. Cl.**  
USPC ..... **D15/28; D34/35**

(58) **Field of Classification Search**  
USPC ..... D15/11, 28, 21, 17, 18; D34/28, 34, 35;  
D14/412, 413, 415, 416, 428;  
D12/174, 179; 74/488, 484 R;  
280/43.12; 187/222, 224; 463/36-38;  
244/234

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

D365,576 S \* 12/1995 Butkovich et al. .... D15/29  
D419,570 S \* 1/2000 Blondeel et al. .... D15/29  
D498,188 S \* 11/2004 Ligneau ..... D12/179  
D498,189 S \* 11/2004 Ligneau ..... D12/179  
D531,942 S \* 11/2006 Chanteloup ..... D12/179  
D537,393 S \* 2/2007 Chanteloup ..... D12/179  
D568,796 S \* 5/2008 Oliver et al. .... D12/179  
D590,848 S \* 4/2009 Umeda et al. .... D15/28  
D595,744 S \* 7/2009 Umeda et al. .... D15/28  
D598,023 S \* 8/2009 Miller et al. .... D14/412

D599,829 S \* 9/2009 Jorgensen et al. .... D15/28  
D606,100 S \* 12/2009 Kobayashi et al. .... D15/28  
D606,566 S \* 12/2009 Kobayashi et al. .... D15/28  
D606,567 S \* 12/2009 Kobayashi et al. .... D15/28  
D628,216 S \* 11/2010 Ulbrich et al. .... D15/28

(Continued)

*Primary Examiner* — Mark Goodwin

(74) *Attorney, Agent, or Firm* — Masuvalley & Partners

(57) **CLAIM**

The ornamental design for a portion of operation grip for machine, as shown and described.


**DESCRIPTION**

FIG. 1 is a first perspective view of the portion of operation grip for machine according to the invention;  
FIG. 2 is a second perspective view of the portion of operation grip for machine of FIG. 1;  
FIG. 3 is a third perspective view of the portion of operation grip for machine of FIG. 1;  
FIG. 4 is a fourth perspective view of the portion of operation grip for machine of FIG. 1;  
FIG. 5 is front elevation view of the portion of operation grip for machine of FIG. 1;  
FIG. 6 is a rear elevation view of the portion of operation grip for machine of FIG. 1;  
FIG. 7 is a right elevation view of the portion of operation grip for machine of FIG. 1;  
FIG. 8 is a left elevation view of the portion of operation grip for machine of FIG. 1;  
FIG. 9 is a top plan view of the portion of operation grip for machine of FIG. 1; and,  
FIG. 10 is a bottom plan view of the portion of operation grip for machine of FIG. 1.

The broken line disclosure, as well as line shading in parts of the drawings are included for the purpose of illustrating use and environment and form no part of the claimed design.

The dot-dash lines shown in the drawings represent the boundary lines of the claimed design.

**1 Claim, 10 Drawing Sheets**



# US D709,102 S

Page 2

---

(56)

## References Cited

### U.S. PATENT DOCUMENTS

D633,111 S \* 2/2011 Muraoka et al. .... D15/28  
D635,155 S \* 3/2011 Blind ..... D15/28  
D635,591 S \* 4/2011 Wahrenberg ..... D15/28

D656,073 S \* 3/2012 Foerster et al. .... D12/179  
D671,565 S \* 11/2012 Kinoshita et al. .... D15/28  
D675,555 S \* 2/2013 Ouellette ..... D12/345  
D678,283 S \* 3/2013 Olson et al. .... D14/412  
D686,622 S \* 7/2013 Rey et al. .... D14/412

\* cited by examiner

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6






FIG. 7




FIG. 8




FIG. 9




FIG. 10

