



US00D712687S

(12) **United States Design Patent**
Arie et al.

(10) **Patent No.:** **US D712,687 S**
(45) **Date of Patent:** **** Sep. 9, 2014**

(54) **RETAIL DISPLAY TRUNK**
 (71) Applicant: **Sony Corporation**, Tokyo (JP)
 (72) Inventors: **Isamu Arie**, Carlsbad, CA (US);
Andrew Glendinning, San Diego, CA (US);
Takayuki Kitahara, San Diego, CA (US);
Naoto Shimizu, San Diego, CA (US)
 (73) Assignee: **Sony Corporation**, Tokyo (JP)
 (**) Term: **14 Years**
 (21) Appl. No.: **29/451,803**
 (22) Filed: **Apr. 9, 2013**
 (51) **LOC (10) Cl.** **06-01**
 (52) **U.S. Cl.**
 USPC **D6/663**
 (58) **Field of Classification Search**
 CPC A47B 87/00; A47B 17/04; A47B 47/03;
 A47F 3/06; A47F 3/043; A47F 3/0434
 USPC D6/663, 664, 677.3, 668, 668.1, 668.2,
 D6/671, 671.1; 297/107, 120, 138.1, 204,
 297/257.1
 See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D101,179 S * 9/1936 Skobel D6/671
 D248,435 S * 7/1978 Densen D6/671.1

(Continued)

Primary Examiner — Mimosa De

(74) *Attorney, Agent, or Firm* — John L. Rogitz

(57) **CLAIM**

The ornamental design for the retail display trunk, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a first embodiment of the retail display trunk in the open configuration from the front of the trunk, showing retail items inside the trunk;
 FIG. 2 is a perspective view of a first embodiment of the retail display trunk in the open configuration from the front of the trunk, with the retail items removed from the trunk;
 FIG. 3 is a perspective view of the first embodiment of the retail display trunk in the open configuration from the back of the trunk;

FIG. 4 is a perspective view of the first embodiment of the retail display trunk in the closed configuration from the front of the trunk;
 FIG. 5 is a top plan view of the first embodiment of the retail display trunk in the open configuration;
 FIG. 6 is a top plan view of the first embodiment of the retail display trunk in the closed configuration;
 FIG. 7 is a bottom plan view of the first embodiment of the retail display trunk in the open configuration;
 FIG. 8 is a bottom plan view of the first embodiment of the retail display trunk in the closed configuration;
 FIG. 9 is a front elevational view of the first embodiment of the retail display trunk in the open configuration;
 FIG. 10 is a front elevational view of the first embodiment of the retail display trunk in the closed configuration;
 FIG. 11 is a side elevational view of the first embodiment of the retail display trunk in the open configuration;
 FIG. 12 is a side elevational view of the first embodiment of the retail display trunk in the closed configuration;
 FIG. 13 is a perspective view of a second embodiment of the retail display trunk in the open configuration from the front of the trunk, showing retail items inside the trunk and speakers arranged in a grid inside the trunk, it being understood that except for the shelving and the retail items the second embodiment is configured the same as the first embodiment;
 FIG. 14 is a perspective view of the second embodiment of the retail display trunk shown in FIG. 13, with the retail items removed;
 FIG. 15 is a perspective view of the second embodiment of the retail display trunk shown in FIG. 14, with the speakers removed;
 FIG. 16 is a perspective view of a third, suitcase-like embodiment of the retail display trunk in the closed configuration;
 FIG. 17 is a perspective view of a fourth embodiment of the retail display trunk in the open configuration from the front of the trunk, showing retail items inside the trunk, it being understood that except for the shelving and the retail items the fourth embodiment is configured the same as the first embodiment;
 FIG. 18 is a perspective view of the fourth embodiment of the retail display trunk shown in FIG. 17, with the retail items removed;
 FIG. 19 is a front plan view of a fifth embodiment of the retail display trunk in the open configuration from the front of the trunk, showing retail items inside the trunk, it being understood that except for the shelving and the retail items the fifth embodiment is configured the same as the first embodiment; and,
 FIG. 20 is a perspective view of the fifth embodiment of the retail display trunk shown in FIG. 19, with the retail items removed.
 The broken lines shown in the drawing are for illustrative purposes only and form no part of the claimed design.

1 Claim, 15 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

D363,618 S * 10/1995 Cramer D6/671.1
D372,607 S * 8/1996 Pallas D6/671.1
D397,262 S * 8/1998 Thomas D6/671
D412,797 S * 8/1999 Sadler D6/663
D445,597 S * 7/2001 Stone et al. D6/671.1
D459,614 S * 7/2002 Grosfillex D6/671.1

D461,653 S * 8/2002 Brinkmann D6/671.1
D467,756 S * 12/2002 Mattick D6/671.1
D530,114 S * 10/2006 Nowotarski et al. D6/671.1
D532,626 S * 11/2006 McDiarmid et al. D6/671.1
D534,010 S * 12/2006 O'Reilly D6/671.1
D534,737 S * 1/2007 Giacometti D6/671.1
D593,772 S * 6/2009 Knight D6/671
D642,400 S * 8/2011 Koehn D6/668.1

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20