



US00D718308S

(12) **United States Design Patent**
Nishizawa

(10) **Patent No.:** **US D718,308 S**

(45) **Date of Patent:** **** Nov. 25, 2014**

(54) **COORDINATE INPUT DEVICE**

(71) Applicant: **Wacom Co., Ltd.**, Kazo-shi, Saitama (JP)

(72) Inventor: **Naoya Nishizawa**, Tokyo (JP)

(73) Assignee: **Wacom Co., Ltd.**, Kazo-shi (JP)

(**) Term: **14 Years**

(21) Appl. No.: **29/469,814**

(22) Filed: **Oct. 15, 2013**

(30) **Foreign Application Priority Data**

Apr. 23, 2013 (JP) 2013-009078

(51) **LOC (10) Cl.** **14-02**

(52) **U.S. Cl.**
USPC **D14/389**

(58) **Field of Classification Search**
USPC D14/388-390, 341-347, 383, 374, 381,
D14/371, 129, 456; 178/18.01,
178/18.03-18.09, 18.11; 345/173-178
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D285,203 S *	8/1986	Milroy et al.	D14/390
D289,291 S *	4/1987	Kapper	D14/389
D321,172 S *	10/1991	Moore et al.	D14/389
D337,322 S *	7/1993	Yang	D14/389
D348,661 S *	7/1994	Hansen et al.	D14/389
D364,389 S *	11/1995	Shimizu	D14/389
D656,137 S *	3/2012	Chung et al.	D14/341
D659,693 S *	5/2012	TerMeer et al.	D14/342
D664,144 S	7/2012	Akana	
D667,404 S *	9/2012	Akana et al.	D14/389
D672,346 S *	12/2012	Shen et al.	D14/341
D690,692 S *	10/2013	Shin	D14/341
D691,132 S *	10/2013	Sharma et al.	D14/341
D712,407 S *	9/2014	Chang	D14/389

OTHER PUBLICATIONS

“G-Pen F509,” © 2013 Genius-KYE Systems, <<http://www.geniustablet.com/EN-Graphic-Tablets-Mouse-Pen-Tablets>>[retrieved Dec. 17, 2013], 1 page.

“Logitech Wireless Rechargeable Touchpad T650,” © 2013 Logitech, <<http://www.logitech.com/en-us/product/touchpad-t650?crd=1153>> [retrieved Dec. 17, 2013], 4 pages.

* cited by examiner

Primary Examiner — Deanna L Pratt

(74) *Attorney, Agent, or Firm* — Christensen O’Connor Johnson Kindness PLLC


(57) **CLAIM**

The ornamental design for a coordinate input device, as shown and described.

DESCRIPTION

FIG. 1 is a bottom front right perspective view of a coordinate input device showing my new design; FIG. 2 is a front elevation view thereof; FIG. 3 is a rear elevation view thereof; FIG. 4 is a top plan view thereof; FIG. 5 is a bottom plan view thereof; FIG. 6 is a left side elevation view thereof; FIG. 7 is a right side elevation view thereof; FIG. 8 is a bottom front right perspective view of an alternative embodiment of the coordinate input device shown in FIG. 1; FIG. 9 is a front elevation view thereof; FIG. 10 is a rear elevation view thereof; FIG. 11 is a top plan view thereof; FIG. 12 is a bottom plan view thereof; FIG. 13 is a left side elevation view thereof; and, FIG. 14 is a right side elevation view thereof. The broken lines shown in FIGS. 4 and 8-14 illustrate portions of the coordinate input device that form no part of the claimed design.

1 Claim, 10 Drawing Sheets






Fig. 1.




Fig. 2.




Fig. 3.




Fig. 4.




Fig. 5.




Fig. 6.




Fig. 7.




Fig. 8.




Fig. 9.




Fig. 10.




Fig. 11.




Fig. 12.




Fig. 13.




Fig. 14.