



US00D719161S

(12) **United States Design Patent**
Huebner

(10) **Patent No.:** **US D719,161 S**
(45) **Date of Patent:** **** Dec. 9, 2014**

(54) **COORDINATE INPUT DEVICE**

FOREIGN PATENT DOCUMENTS

(71) Applicant: **Wacom Co., Ltd.**, Kazo-shi, Saitama (JP)

JP D1446815 S 7/2012
JP D1450316 S 9/2012
JP D1450317 S 9/2012

(72) Inventor: **Volker Huebner**, Erkrath (DE)

Primary Examiner — Deanna L Pratt

(73) Assignee: **Wacom Co., Ltd.**, Kazo-shi (JP)

(74) *Attorney, Agent, or Firm* — Christensen O'Connor Johnson Kindness PLLC

(**) Term: **14 Years**

(21) Appl. No.: **29/460,813**

(57) **CLAIM**

(22) Filed: **Jul. 15, 2013**

The ornamental design for a coordinate input device, as shown and described.

(30) **Foreign Application Priority Data**

Jan. 18, 2013 (JP) 2013-000804

(51) **LOC (10) Cl.** **14-02**

(52) **U.S. Cl.**
USPC **D14/389**

(58) **Field of Classification Search**
USPC D14/388–390, 341–347, 383, 374, 381,
D14/371, 129, 456; 178/18.01,
178/18.03–18.09, 18.11; 345/173–178
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS


D524,308 S * 7/2006 Lai D14/346
D602,488 S * 10/2009 Jiang et al. D14/341
D629,400 S * 12/2010 Harper D14/390
D629,401 S * 12/2010 Crisp et al. D14/390
D629,402 S * 12/2010 Crisp et al. D14/390
D631,047 S * 1/2011 Hirota D14/390
D642,174 S * 7/2011 Hirota D14/390
D645,036 S * 9/2011 Jones et al. D14/341
D645,038 S * 9/2011 Tzeng D14/341
D648,723 S * 11/2011 Harper et al. D14/390
D654,497 S * 2/2012 Lee D14/341
D671,117 S 11/2012 Harper
D690,696 S 10/2013 Jonsson

(Continued)

DESCRIPTION

FIG. 1 is a bottom front right perspective view of a coordinate input device showing my new design; FIG. 2 is a front elevation view thereof; FIG. 3 is a rear elevation view thereof; FIG. 4 is a left side elevation view thereof; FIG. 5 is a right side elevation view thereof; FIG. 6 is a top plan view thereof; FIG. 7 is a bottom plan view thereof; FIG. 8 is a cross-sectional view along line 8-8 in FIG. 2; FIG. 9 is a cross-sectional view along line 9-9 in FIG. 2; FIG. 10 is a bottom front right perspective view of an alternative embodiment of the coordinate input device shown in FIG. 1; FIG. 11 is a front elevation view thereof; FIG. 12 is a rear elevation view thereof; FIG. 13 is a left side elevation view thereof; FIG. 14 is a right side elevation view thereof; FIG. 15 is a top plan view thereof; and, FIG. 16 is a bottom plan view thereof. The broken lines shown in FIGS. 10-16 illustrate portions of the coordinate input device that form no part of the claimed design.

1 Claim, 8 Drawing Sheets



US D719,161 S

Page 2

(56)

References Cited

U.S. PATENT DOCUMENTS

D690,697 S 10/2013 Jonsson
D690,698 S * 10/2013 Jonsson et al. D14/390
D690,699 S * 10/2013 Jonsson et al. D14/390

D690,700 S 10/2013 Jonsson
D690,701 S * 10/2013 Jonsson D14/390
D702,235 S * 4/2014 Jonsson et al. D14/390
D712,400 S * 9/2014 Kim et al. D14/341
2013/0161179 A1 * 6/2013 Tamura et al. 200/600

* cited by examiner





Fig. 1.






Fig. 3.




Fig. 4.




Fig. 5.




Fig. 6.




Fig. 7.




Fig. 8.




Fig. 9.




Fig. 10.




Fig. 11.




Fig. 12.




Fig. 13.



Fig. 14.




Fig. 15.




Fig. 16.