



US00D720683S

(12) **United States Design Patent**
Boore et al.

(10) **Patent No.:** **US D720,683 S**

(45) **Date of Patent:** **** Jan. 6, 2015**

(54) **TIRE**

(71) Applicant: **The Goodyear Tire & Rubber Company, Akron, OH (US)**

(72) Inventors: **Robert Edgar Boore, Uniontown, OH (US); Jonathan James Shondel, Massillon, OH (US)**

(73) Assignee: **The Goodyear Tire & Rubber Company, Akron, OH (US)**

(**) Term: **14 Years**

(21) Appl. No.: **29/433,594**

(22) Filed: **Oct. 2, 2012**

(51) **LOC (10) Cl.** **12-15**

(52) **U.S. Cl.**
USPC **D12/563**

(58) **Field of Classification Search**
USPC D12/533-567; 152/209.1-209.9
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D389,790 S	1/1998	Himuro	D12/147
D400,830 S	* 11/1998	Gerresheim et al.	D12/551
D409,123 S	5/1999	Heinen et al.	D12/151
D414,728 S	10/1999	Gerresheim et al.	D12/147
D437,808 S	2/2001	Gerresheim et al.	D12/147
D438,827 S	3/2001	Gerresheim et al.	D12/147
D442,524 S	5/2001	Gerresheim et al.	D12/147
D452,198 S	12/2001	Heinen et al.	D12/146
D456,764 S	5/2002	Heinen et al.	D12/551
D471,152 S	3/2003	Graas et al.	D12/563
D486,123 S	2/2004	Heinen et al.	D12/550
D491,518 S	6/2004	Miyabe et al.	D12/556
D495,991 S	* 9/2004	Chatignoux	D12/563
D504,866 S	5/2005	Collette et al.	D12/553
D505,111 S	5/2005	Allison et al.	D12/563
D505,383 S	5/2005	Ratliff, Jr. et al.	D12/551
D508,017 S	8/2005	Heinen et al.	D12/555

D525,192 S	7/2006	Shondel et al.	D12/552
D526,955 S	8/2006	Heinen et al.	D12/549
D559,770 S	1/2008	Blackiston et al.	D12/555
D582,840 S	12/2008	Bombardier et al.	D12/550
D583,305 S	12/2008	Ashton et al.	D12/553
D589,434 S	3/2009	Behr et al.	D12/553
D589,435 S	3/2009	Ashton et al.	D12/563
D596,558 S	7/2009	de Briey-Terlinden	D12/553
D612,324 S	3/2010	Harvey et al.	D12/551
D641,306 S	7/2011	Graas et al.	D12/551
D642,507 S	8/2011	Heinen et al.	D12/555

* cited by examiner

Primary Examiner — George D Kirschbaum

(74) *Attorney, Agent, or Firm* — Richard B. O'Planick

(57) **CLAIM**

The ornamental design for a tire, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a tire showing our new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread;

FIG. 2 is a front elevational view thereof;



FIG. 3 is a right side elevational view thereof; the other side being a mirror image thereof;

FIG. 4 is an enlarged fragmentary front elevational view thereof;

FIG. 5 is a perspective view of a second embodiment of a tire showing our new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread and that the opposite side view is a mirror image thereof; and, FIG. 6 is a front elevational view of a second embodiment, it being understood that an enlarged fragmentary view thereof would be substantially identical to that shown in FIG. 4, with the exception of the inclusion of the sidewall in solid lines.

In the drawings, the broken lines showing of the sidewall, inner bead and the peripheral boundary between the tire tread and the sidewall in FIGS. 1 through 4 depict environmental subject matter and form no part of the claimed design.

1 Claim, 6 Drawing Sheets






FIG-1




FIG-2




FIG-3




FIG-4




FIG-5




FIG-6