



US00D721221S

(12) **United States Design Patent**
Frink, Sr.

(10) **Patent No.:** **US D721,221 S**

(45) **Date of Patent:** **** Jan. 20, 2015**

(54) **NECK TIE**

(71) Applicant: **Cleave Frink, Sr.**, Melbourne, FL (US)

(72) Inventor: **Cleave Frink, Sr.**, Melbourne, FL (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/487,392**

(22) Filed: **Apr. 8, 2014**

(51) **LOC (10) Cl.** **02-05**

(52) **U.S. Cl.**
USPC **D2/605**

(58) **Field of Classification Search**
USPC D2/500, 501, 502, 503, 504, 505, 506,
D2/507, 508, 600, 601, 602, 604, 605, 606,
D2/607, 608, 609, 881; D29/108;
D30/145, 151, 152; 2/129, 140, 144,
2/145, 146, 147, 148, 149, 207
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

446,253	A *	2/1891	Eschner	2/148
828,967	A *	8/1906	Reichblum	2/91
D170,598	S *	10/1953	Neumann	D2/500
D179,831	S *	3/1957	Young	D2/500
4,468,818	A *	9/1984	Flannery	2/207
D309,212	S *	7/1990	Maletsky et al.	D2/602
D327,339	S *	6/1992	Rasmussen et al.	D29/108
D381,786	S *	8/1997	Arakawa	D2/605
D423,150	S *	4/2000	Vignere	D30/145
D425,263	S *	5/2000	Hanada	D30/145
6,256,793	B1 *	7/2001	Arias et al.	2/207
D490,193	S *	5/2004	D'Anza	D30/145
D515,250	S *	2/2006	Story	D30/145
D515,278	S *	2/2006	Jendrucko et al.	D2/500
D542,481	S *	5/2007	Katz	D30/145

7,427,417	B2 *	9/2008	Jendrucko et al.	424/725
7,636,953	B2 *	12/2009	Grey	2/207
D623,827	S *	9/2010	Pauling	D2/605
D672,453	S *	12/2012	Lannan et al.	D24/110.1
D688,850	S *	9/2013	Parker	D2/881
2003/0070208	A1 *	4/2003	Magdziak-Hautala	2/207
2008/0092268	A1 *	4/2008	Mangham	2/129
2008/0184996	A1 *	8/2008	Colorado	128/201.25

* cited by examiner

Primary Examiner — Karen E Eldridge Powers

(74) *Attorney, Agent, or Firm* — Mark R. Malek; Widerman Malek, PL

(57) **CLAIM**

The ornamental design for a neck tie, as shown and described.

DESCRIPTION

FIG. 1 is a front perspective view of a neck tie according to the present invention.

FIG. 2 is a front perspective view of the neck tie illustrated in FIG. 1 and showing fastening elements in a disengaged position.

FIG. 3 is a front elevation view of the neck tie illustrated in FIG. 1.

FIG. 4 is a rear elevation view of the neck tie illustrated in FIG. 1.

FIG. 5 is a top plan view of the neck tie illustrated in FIG. 1.


FIG. 6 is a bottom plan view of the neck tie illustrated in FIG. 1.

FIG. 7 is a left side elevation view of the neck tie illustrated in FIG. 1; and,

FIG. 8 is a right side elevation view of the neck tie illustrated in FIG. 1.

The broken lines depict fastening elements of the neck tie that do not form a claimed feature of the present invention.

1 Claim, 3 Drawing Sheets






Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7



Fig. 8