



US00D721638S

(12) **United States Design Patent**
Knispel

(10) **Patent No.:** **US D721,638 S**
(45) **Date of Patent:** **** Jan. 27, 2015**

(54) **TIRE**

(75) Inventor: **Oliver Knispel**, Gelnhausen-Hailer (DE)

(73) Assignee: **The Goodyear Tire & Rubber Company**, Akron, OH (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/429,823**

(22) Filed: **Aug. 17, 2012**

(51) **LOC (10) Cl.** **12-15**

(52) **U.S. Cl.**
USPC **D12/564**

(58) **Field of Classification Search**
USPC D12/533–567; 152/209.1–209.9
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D362,420 S	9/1995	Heinen et al.	D12/147
D379,448 S	5/1997	Graas et al.	D12/147
D387,714 S	12/1997	Heinen	D12/147
D429,194 S	8/2000	Heinen et al.	D12/147
D429,478 S	8/2000	Heinen et al.	D12/147
D431,800 S	10/2000	Heinen et al.	D12/147
D441,328 S	5/2001	Heinen et al.	D12/146
D441,695 S	5/2001	Heinen et al.	D12/147
D446,170 S *	8/2001	Williams	D12/550
D450,293 S *	11/2001	Williams	D12/565
D451,068 S	11/2001	Heinen et al.	D12/547
D452,198 S	12/2001	Heinen et al.	D12/146
D504,106 S	4/2005	de Briey-Terlinden et al.	D12/553
D504,866 S	5/2005	Collette et al.	D12/553
D505,112 S	5/2005	Heinen et al.	D12/567
D512,682 S *	12/2005	Krenz et al.	D12/564
D556,670 S	12/2007	Fontaine et al.	D12/553
D575,726 S	8/2008	Fontaine et al.	D12/564
D589,874 S	4/2009	Fontaine et al.	D12/564
D591,221 S	4/2009	Fontaine et al.	D12/563

D591,672 S	5/2009	de Briey-Terlinden et al.	D12/553
D592,588 S	5/2009	Heinen et al.	D12/564
D595,639 S	7/2009	de Briey-Terlinden	D12/553
D595,640 S	7/2009	de Briey-Terlinden	D12/564
D596,109 S	7/2009	de Briey-Terlinden	D12/553
D597,475 S	8/2009	Heinen et al.	D12/553
D597,476 S	8/2009	de Briey-Terlinden	D12/553
D600,195 S	9/2009	Fontaine et al.	D12/564
D601,946 S	10/2009	Fontaine et al.	D12/553
D606,007 S	12/2009	Fontaine et al.	D12/564
D610,964 S	3/2010	Dixon et al.	D12/552

(Continued)

Primary Examiner — George D Kirschbaum

(74) *Attorney, Agent, or Firm* — Richard B. O'Planick

(57) **CLAIM**

The ornamental design for a tire, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a tire showing my new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread;

FIG. 2 is a front elevational view thereof;



FIG. 3 is a right side elevational view thereof; the other side being a mirror image thereof;

FIG. 4 is an enlarged fragmentary front elevational view thereof;

FIG. 5 is a perspective view of a second embodiment of a tire showing my new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread and that the opposite side view is a mirror image thereof; and, FIG. 6 is a front elevational view of a second embodiment, it being understood that an enlarged fragmentary view thereof would be substantially identical to that shown in FIG. 4, with the exception of the inclusion of the sidewall in solid lines.

In the drawings, the broken lines showing of the sidewall, inner bead and the peripheral boundary between The tire tread and the sidewall in FIGS. 1 through 4 depict environmental subject matter and form no part of the claimed design.

1 Claim, 6 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

D635,912 S * 4/2011 Knispel D12/564

D638,350 S * 5/2011 Knispel D12/564

D640,184 S 6/2011 de Briey-Terlinden D12/553

D640,966 S 7/2011 Fontaine et al. D12/563

D641,305 S 7/2011 de Briey-Terlinden D12/547

D702,625 S * 4/2014 Leconte et al. D12/564

* cited by examiner




FIG-1




FIG-2




FIG-3




FIG-4



FIG-5




FIG-6