

US00D723091S

(12) **United States Design Patent**
Hale

(10) **Patent No.:** **US D723,091 S**
(45) **Date of Patent:** **** Feb. 24, 2015**

(54) **BALL TRIPOD**

(75) Inventor: **Eric C. Hale**, San Francisco, CA (US)

(73) Assignee: **Daymen US, Inc.**, Petaluma, CA (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/427,734**

(22) Filed: **Jul. 21, 2012**

(51) **LOC (10) Cl.** **16-05**

(52) **U.S. Cl.**
USPC **D16/244**

(58) **Field of Classification Search**
USPC D15/28; D16/237, 240, 242–245, 250;
89/40.06; 108/147.22; 248/157, 163.1,
248/166–168, 171, 173, 176.3, 177.1,
248/181.1, 183.1, 183.2, 185.1, 186.2,
248/188.5, 346.3, 357, 524, 528, 586;
254/1; 280/47.32; 352/243; 396/428;
403/300, 348, 349

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,548,659	A *	4/1951	Epprecht	248/181.1
5,116,005	A *	5/1992	LaGoy	248/168
D349,914	S *	8/1994	Usui	D16/244
D350,970	S *	9/1994	Usui	D16/244
5,708,890	A *	1/1998	Nakano	396/428
6,068,224	A *	5/2000	Horiuchi	248/187.1
D445,123	S *	7/2001	Shen	D16/244
2005/0178935	A1 *	8/2005	Brandes	248/177.1
2008/0191105	A1 *	8/2008	Bogel	248/170
2012/0269503	A1 *	10/2012	Hale	396/428

FOREIGN PATENT DOCUMENTS

EM 002155614-0001 * 12/2012

OTHER PUBLICATIONS

<http://www.amazon.de/Joby-GorillaPod-Micro-handliche-Kamerastative/dp/B005I4928O> Product Available beginning Dec. 20, 2011.*

<http://www.amazon.co.uk/Joby-JB01096-BWW-Micro-Camera-Tripod/dp/B006O4NB34> Product Available beginning Dec. 30, 2011.*

<http://www.cyfrowe.pl/aparaty/statyw-joby-gorillapod-micro250-czarno-szary.html> Originally posted on website Jan. 19, 2012.*

* cited by examiner

Primary Examiner — Susan Bennett Hattan

Assistant Examiner — Leanne Was

(74) *Attorney, Agent, or Firm* — Michael A. Guth

(57) **CLAIM**

The ornamental design for a ball tripod, as shown and described.

DESCRIPTION

FIG. 1 is a front view of a ball tripod in a closed configuration. FIG. 2 is a back view of a ball tripod in a closed configuration. FIG. 3 is a right side view of a ball tripod in a closed configuration.

FIG. 4 is a left side view of a ball tripod in a closed configuration.

FIG. 5 is a bottom view of a ball tripod in a closed configuration.

FIG. 6 is a top view of a ball tripod in a closed configuration.

FIG. 7 is a front view of a ball tripod in an open configuration.


FIG. 8 is a back view of a ball tripod in an open configuration.

FIG. 9 is a left side view of a ball tripod in an open configuration. The right side view is a mirror image.

FIG. 10 is a bottom view of a ball tripod in an open configuration; and,

FIG. 11 is a top view of a ball tripod in an open configuration. The broken lines depict unclaimed portions of the ball tripod.

1 Claim, 10 Drawing Sheets






FIGURE 1




FIGURE 2




FIGURE 3




FIGURE 4




FIGURE 5




FIGURE 6




FIGURE 7




FIGURE 8




FIGURE 9




FIGURE 10