



US00D725600S

(12) **United States Design Patent**
Fujikata et al.

(10) **Patent No.:** **US D725,600 S**
(45) **Date of Patent:** **** Mar. 31, 2015**

(54) **ELECTRICAL CONTACT FOR USE IN A
PLATING APPARATUS**

- (71) Applicant: **Ebara Corporation**, Tokyo (JP)
- (72) Inventors: **Jumpei Fujikata**, Tokyo (JP); **Masaaki Kimura**, Tokyo (JP); **Mitsutoshi Yahagi**, Tokyo (JP)
- (73) Assignee: **Ebara Corporation**, Tokyo (JP)
- (**) Term: **14 Years**
- (21) Appl. No.: **29/488,445**
- (22) Filed: **Apr. 18, 2014**

Related U.S. Application Data

- (60) Continuation-in-part of application No. 29/488,146, filed on Apr. 16, 2014, which is a division of application No. 29/463,693, filed on Jan. 28, 2014, now Pat. No. Des. 717,736, which is a division of application No. 29/462,320, filed on Aug. 1, 2013, now Pat. No. Des. 706,224.

(30) **Foreign Application Priority Data**

- Mar. 4, 2014 (JP) 2014-004595
- Mar. 4, 2014 (JP) 2014-004596
- Mar. 4, 2014 (JP) 2014-004597

- (51) **LOC (10) Cl.** **13-03**

- (52) **U.S. Cl.**
USPC **D13/154**

- (58) **Field of Classification Search**
USPC D13/147, 154, 184, 194; 439/607.01, 439/607.04, 607.05, 607.17, 607.25, 439/607.34, 607.41, 607.53, 623, 660, 668, 439/680, 792, 839, 842, 843, 845, 846, 849, 439/850, 865, 866, 867, 868, 869, 870, 871, 439/872, 873, 874, 875, 876, 877, 878, 879, 439/880, 881, 882, 883, 884, 885, 886, 887, 439/888, 889, 890, 891, 892

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

- 6,500,012 B1 * 12/2002 Billenstein et al. 439/92
- D519,931 S * 5/2006 Van Haaster D13/153

(Continued)

Primary Examiner — Daniel Bui

(74) *Attorney, Agent, or Firm* — Pearne & Gordon LLP


(57) **CLAIM**

The ornamental design for an electrical contact for use in a plating apparatus, as shown and described.

DESCRIPTION

FIG. 1 is a front perspective view of a electrical contact for use in a plating apparatus showing our new design;
 FIG. 2 is a rear perspective view thereof;
 FIG. 3 is a front elevation view thereof;
 FIG. 4 is a bottom plan view thereof;
 FIG. 5 is a top plan view thereof;
 FIG. 6 is a rear elevation view thereof;
 FIG. 7 is a right side elevation view thereof;
 FIG. 8 is a is a front perspective view of a second electrical contact for use in a plating apparatus showing our new design;
 FIG. 9 is a rear perspective view thereof;
 FIG. 10 is a front view thereof;
 FIG. 11 is a bottom view thereof;
 FIG. 12 is a plan view thereof;
 FIG. 13 is a rear view thereof;
 FIG. 14 is a right side view thereof;
 FIG. 15 is a front perspective view of a third electrical contact for use in a plating apparatus showing our new design;
 FIG. 16 is a rear perspective view thereof;
 FIG. 17 is a front view thereof;
 FIG. 18 is a bottom view thereof;
 FIG. 19 is a plan view thereof;
 FIG. 20 is a rear view thereof; and,
 FIG. 21 is a right side view thereof.

1 Claim, 6 Drawing Sheets



US D725,600 S

Page 2

(56)

References Cited

U.S. PATENT DOCUMENTS

D556,692 S 12/2007 Yahagi et al.

D651,178 S 12/2011 Fujikata et al.
D669,439 S 10/2012 Fujikata et al.
D706,224 S * 6/2014 Kimura et al. D13/154

* cited by examiner

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20



FIG. 21

