



US00D726035S

(12) **United States Design Patent**
Perez et al.

(10) **Patent No.:** **US D726,035 S**
(45) **Date of Patent:** **** Apr. 7, 2015**

(54) **WIRELESS SIGNAL SENSOR**

702/154, 127, 131, 182, 183, 189; 600/437,
600/443, 453, 459, 465, 479, 500, 502, 595,
600/485, 481, 483

(71) Applicant: **Nokia Corporation**, Espoo (FI)

See application file for complete search history.

(72) Inventors: **Jose Perez**, Helsinki (FI); **Jukka Rautiainen**, Helsinki (FI)

(56) **References Cited**

(73) Assignee: **Nokia Corporation**, Espoo (FI)

U.S. PATENT DOCUMENTS

(**) Term: **14 Years**

D274,796 S * 7/1984 Humble D10/106.91
D675,946 S * 2/2013 Chan D10/65
D692,784 S * 11/2013 Anderssen et al. D10/70
D693,248 S * 11/2013 Anderssen et al. D10/65
D694,658 S * 12/2013 Avidor et al. D10/65

(21) Appl. No.: **29/461,099**

* cited by examiner

(22) Filed: **Jul. 18, 2013**

(51) **LOC (10) Cl.** **10-04**

Primary Examiner — Antoine D Davis

(52) **U.S. Cl.**

(74) *Attorney, Agent, or Firm* — Banner & Witcoff, Ltd.

USPC **D10/65**; D10/70; D10/78

(58) **Field of Classification Search**

(57) **CLAIM**


The ornamental design for a wireless signal sensor, as shown and described.

CPC G08G 1/096883; G08G 1/096872;
G08G 1/096775; G01C 21/16; G01C 21/3688;
G01C 21/30; G01C 21/265; G01C 21/26;
G01C 21/00; G01C 21/3632; G01C 21/3617;
G01C 25/005; G01C 21/3664; G01P 3/22;
G01P 3/50; G01P 15/18; G06F 3/00
USPC D10/65, 70, 75, 78; D14/138 R, 138 AA,
D14/138 AB, 138 AC, 138 AD, 341–347,
D14/507–510, 136, 137, 167, 168, 496, 498,
D14/499, 500, 125–134, 239, 371, 374–377,
D14/440, 450, 448, 336; 343/702; 345/87,
345/104, 133, 156, 168, 173, 901–905,
345/165; 348/180, 184, 315, 739, 836, 838,
348/325; 364/444, 499; 701/408–418, 431,
701/432, 537; 312/7.2; 341/12; 720/605,
720/669, 600, 655; 369/99, 197; 455/344,
455/347, 575.1; 250/221, 338.3, 340, 239,
250/342, 341, DIG. 1, 353; 307/116, 117;
340/521, 527, 541, 567, 540, 568.2,
340/539.23, 635, 687; 315/159; 324/72.5,
324/556, 133, 149, 503, 543, 555, 66, 72,
324/754, 115, 141, 522; 73/615, 624, 627,
73/644, 514.33, 514.34, 510, 513, 527,
73/530; 356/3.01–5.15; 235/105; 377/5,
377/24.2, 26; 702/155, 160, 176, 78, 79,
702/82, 91–95, 104, 116, 141, 150, 151,

DESCRIPTION

FIG. 1 is a front perspective view of a first embodiment of a wireless signal sensor showing our new design;
FIG. 2 is a front view thereof;
FIG. 3 is a rear view thereof;
FIG. 4 is a left side view thereof;
FIG. 5 is a right side view thereof;
FIG. 6 is a top view thereof;
FIG. 7 is a bottom view thereof;
FIG. 8 is a front perspective view of a second embodiment of a wireless signal sensor showing our new design;
FIG. 9 is a front view thereof;
FIG. 10 is a rear view thereof;
FIG. 11 is a left side view thereof;
FIG. 12 is a right side view thereof;
FIG. 13 is a top view thereof; and,
FIG. 14 is a bottom view thereof.
The broken line showing of the wireless signal sensor in the Figures are for illustrative purposes only and form no part of the claimed design.

1 Claim, 10 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14