US00D726126S

(12) United States Design Patent

Rizzi et al.

(10) Patent No.: US D726,126 S
(45) Date of Patent: ** Apr. 7, 2015

(54) **SWITCHING DEVICE FOR AN ELECTRICAL SWITCHGEAR**

(71) Applicant: **ABB Technology AG**, Zurich (CH)

(72) Inventors: **Corrado Rizzi**, Fornovo S. Guiovanni (IT); **Francesco Belloni**, Bergamo (IT)

(73) Assignee: **ABB Technology AG**, Zurich (CH)

(**) Term: **14 Years**

(21) Appl. No.: **29/444,382**

(22) Filed: **Jan. 30, 2013**

(30) **Foreign Application Priority Data**

Jul. 31, 2012 (EM) 002081570

(51) **LOC (10) Cl.** **13-03**

(52) **U.S. Cl.**
USPC **D13/158**

(58) **Field of Classification Search**
CPC H01H 31/28; H01H 33/022; H01H 33/66207; H01H 33/666; H01H 33/6661; H01H 33/027; H01H 33/56; H01H 33/6662; H01H 3/40; H01H 3/46; H01H 9/02; H01H 2033/6667; H01H 2033/6623; H01H 1/5822; H01H 2009/526; H01H 2033/024; H01H 2033/566; H01H 2033/568; H01H 2033/6665; H01H 31/32; H01H 33/127; H01H 33/38; H02B 5/00
USPC ..... D13/123, 125, 158, 160, 162, 164, 171, D13/159; 439/417–419, 395–404, 465, 695, 439/696, 701; D32/60, 61; 338/179, 198; 174/50, 66, 65 R, 67, 70 R, 77 R, 77 S, 174/92; 200/5 R, 43.11, 43.14, 50.01, 50.15, 200/293, 293.1, 303, 401; 361/42, 44, 45, 361/50, 71, 115, 118, 119, 679; 335/374, 335/68, 132, 202; 15/230.11; 401/121, 127, 401/137, 146, 197; D4/122, 123; D8/373–386; 218/118, 119, 7, 77, 78, 218/79, 2, 102; 251/172
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,527,028 A * 7/1985 Luehring 218/119
6,198,062 B1 * 3/2001 Mather et al. 218/152

(Continued)

FOREIGN PATENT DOCUMENTS

CN 2007-20305137.3 12/2008
CN 2010-2012736.3 4/2011

(Continued)

OTHER PUBLICATIONS

ABB Catalogue, "SFG Gas-insulated indoor switch disconnector", Release date 2009.

Primary Examiner — Thomas Johannes
Assistant Examiner — Shawn T Gingrich
(74) *Attorney, Agent, or Firm* — Novak Druce Connolly Bove + Quigg LLP

(57) **CLAIM**

The ornamental design for switching device for an electrical switchgear, as shown ad described.

DESCRIPTION

FIG. **1** is a isometric view of a switching device for an electrical switchgear showing our new design;
FIG. **2** is a front view thereof;
FIG. **3** is a rear view thereof;
FIG. **4** is a left view thereof;
FIG. **5** is a right view thereof;
FIG. **6** is a top view thereof; and,
FIG. **7** is a bottom view thereof.
The broken line portion of the figure drawings is included to show unclaimed subject matter only and forms no part of the claimed design.

1 Claim, 7 Drawing Sheets



(56) **References Cited**

U.S. PATENT DOCUMENTS

D583,332	S *	12/2008	Shang	D13/158
8,440,930	B2 *	5/2013	Lee	218/140
D686,165	S *	7/2013	Bullock et al.	D13/158
D692,839	S *	11/2013	Shang	D13/158
D693,313	S *	11/2013	Bullock et al.	D13/158
D698,321	S *	1/2014	Arioka et al.	D13/160
D703,152	S *	4/2014	Holaus et al.	D13/158
8,729,985	B2 *	5/2014	Bullock et al.	335/120
2007/0261946	A1 *	11/2007	Yu	200/48 R
2011/0155697	A1 *	6/2011	Lee	218/140
2013/0187733	A1 *	7/2013	Bullock et al.	335/13
2013/0248338	A1 *	9/2013	Belloni et al.	200/5 A

FOREIGN PATENT DOCUMENTS

DE	20 2010 005 246	U1	9/2010
EP	1928065	A1	6/2008
RU	99899	U1	11/2010

* cited by examiner



FIGURE 1



FIGURE 2



FIGURE 3

FIGURE 4



FIGURE 5





FIGURE 6



FIGURE 7