



US00D728927S

(12) **United States Design Patent**
Dumas

(10) **Patent No.:** **US D728,927 S**
(45) **Date of Patent:** **** May 12, 2015**

(54) **BAG**

DESCRIPTION

(71) Applicant: **Hermes Sellier (Societe par Actions Simplifiee)**, Paris (FR)

(72) Inventor: **Pierre-Alexis Dumas**, Paris (FR)

(73) Assignee: **Hermes Sellier (Societe par Actions Simplifiee)**, Paris (FR)

(**) Term: **14 Years**

(21) Appl. No.: **29/479,661**

(22) Filed: **Jan. 17, 2014**

(30) **Foreign Application Priority Data**

Jul. 19, 2013 (WO) DM/081 375

(51) **LOC (10) Cl.** **03-01**

(52) **U.S. Cl.**
USPC **D3/245**

(58) **Field of Classification Search**

CPC A45C 1/024; A45C 3/06

USPC D3/232-233, 240-243, 245-246

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D31,053 S * 6/1899 Lehman D3/241
D129,753 S * 9/1941 Tashman D3/241

(Continued)

Primary Examiner — Holly Baynham

(74) *Attorney, Agent, or Firm* — Foley & Lardner LLP

(57) **CLAIM**

The ornamental design for a bag, as shown and described.

FIG. 1 is a front view of the bag of the claimed design, with outer handles thereof in a first outer handle position; FIG. 2 is a back view of the bag shown in FIG. 1, with the outer handles thereof in the first outer handle position; FIG. 3 is a right side view of the bag shown in FIG. 1, with the outer handles thereof in the first outer handle position; FIG. 4 is a left side view of the bag shown in FIG. 1, with the outer handles thereof in the first outer handle position; FIG. 5 is a top view of the bag shown in FIG. 1, with the outer handles thereof in the first outer handle position and inner handles thereof in a first inner handle position; FIG. 6 is a first perspective view of the bag shown in FIG. 1, with the outer handles thereof in the first outer handle position and inner handles thereof in the first inner handle position; FIG. 7 is a bottom view of the bag shown in FIG. 1; FIG. 8 is a front view of the bag shown in FIG. 1, with the outer handles thereof in a second outer handle position and the inner handles thereof in a second inner handle position; FIG. 9 is a back view of the bag shown in FIG. 1, with the outer handles thereof in the second outer handle position and the inner handles thereof in the second inner handle position; FIG. 10 is a right side view of the bag shown in FIG. 1, with the outer handles thereof in the second outer handle position and the inner handles thereof in the second inner handle position; FIG. 11 is a left side view of the bag shown in FIG. 1, with the outer handles thereof in the second outer handle position and the inner handles thereof in the second inner handle position; FIG. 12 is a top view of the bag shown in FIG. 1, with the outer handles thereof in the second outer handle position and the inner handles thereof in the second inner handle position; and, FIG. 13 is a second perspective view of the bag shown in FIG. 1, with the outer handles thereof in the second outer handle position and the inner handles thereof in the second inner handle position.

1 Claim, 13 Drawing Sheets



US D728,927 S

Page 2

(56)

References Cited

U.S. PATENT DOCUMENTS

D497,716 S	*	11/2004	de Baschmakoff	D3/241	
D559,542 S	*	1/2008	Nair	D3/246	* cited by examiner
D564,228 S	*	3/2008	Morelli	D3/246	
D668,041 S	*	10/2012	Kriemler	D3/232	
D715,543 S	*	10/2014	Dumas	D3/245	



FIG. 1



FIG. 2



FIG. 3



FIG. 4




FIG. 5



FIG. 6



FIG. 7



FIG. 8



FIG. 9



FIG. 10



FIG. 11



FIG. 12



FIG. 13