

US00D728936S

(12) **United States Design Patent**
Davis

(10) **Patent No.:** **US D728,936 S**
(45) **Date of Patent:** **** May 12, 2015**

(54) **COMBINED PROTECTIVE CUFFED
JEWELRY SLEEVE AND SECURED
JEWELRY DISPLAY BOARD INSERT**

DESCRIPTION

(71) Applicant: **Shirley Mae Davis**, Dayton, OH (US)

(72) Inventor: **Shirley Mae Davis**, Dayton, OH (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/442,757**

(22) Filed: **May 7, 2013**

(51) **LOC (10) Cl.** **03-01**

(52) **U.S. Cl.**
USPC **D3/299**

(58) **Field of Classification Search**
CPC B65D 1/34; B65D 73/00; B65D 76/30
USPC D3/299; 206/566, 216, 6.1; 150/100,
150/103-110, 113-114, 117-119
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,401,219	A *	8/1983	Mink	206/566
D458,752	S *	6/2002	Wolf	D3/299
D471,011	S *	3/2003	Kowalsky	D3/299
D473,715	S *	4/2003	Moldovan	D3/299
D621,780	S *	8/2010	Ferber et al.	D13/108
D646,485	S *	10/2011	Mason	D3/299

* cited by examiner

Primary Examiner — Holly Baynham

(74) *Attorney, Agent, or Firm* — Dinsmore & Shohl LLP

(57) **CLAIM**

I claim the ornamental design for a combined protective cuffed jewelry sleeve and secured jewelry display board insert, as shown and described.

FIG. 1 is a front elevational view of a combined protective cuffed jewelry sleeve and secured jewelry display board insert with the display board element removed from the jewelry sleeve element illustrating an embodiment of my new design;

FIG. 2 is a front perspective view thereof;

FIG. 3 is a front elevational view thereof with the display board element disposed within the jewelry sleeve element;

FIG. 4 is a front elevational view thereof with the protective cuff lifted to show a concealed handle underneath;

FIG. 5 is a rear perspective view thereof;

FIG. 6 is a rear perspective view thereof with a loop having mesh attached thereto flipped out of the jewelry sleeve element;

FIG. 7 is a front perspective view thereof;

FIG. 8 is a front elevational view thereof with the protective cuff inverted to close the jewelry sleeve element and reveal the handle;

FIG. 9 is a rear elevational view thereof;

FIG. 10 is a top perspective view thereof;

FIG. 11 is a front perspective view thereof with the display board element removed from the jewelry sleeve element;

FIG. 12 is a bottom perspective view of the display board element thereof;

FIG. 13 is a top perspective view thereof;

FIG. 14 is a front elevational view thereof;

FIG. 15 is a front perspective view thereof with clasp loops partially unfurled;


FIG. 16 is a front elevational view thereof with a single clasp loop partially unfurled;

FIG. 17 is a rear perspective view thereof with clasp loops partially unfurled; and,

FIG. 18 is a rear elevational view thereof with clasp loops secured.

The elements of the claimed design are shown detached for clarity of illustration.

1 Claim, 18 Drawing Sheets






FIG. 1




FIG. 2



FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18