



US00D729052S

(12) **United States Design Patent**
Summers et al.

(10) **Patent No.:** **US D729,052 S**

(45) **Date of Patent:** **** May 12, 2015**

(54) **CAPTIVE SCREW**

(75) Inventors: **Gregg Vincent Summers**, Scottsdale, AZ (US); **Alwin Golosinda Guittard**, Litchfield Park, AZ (US)

(73) Assignee: **Penninsula Components, Inc.**, San Carlos, CA (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/427,140**

(22) Filed: **Jul. 13, 2012**

(51) **LOC (10) Cl.** **08-08**

(52) **U.S. Cl.**
USPC **D8/387**

(58) **Field of Classification Search**
USPC D8/382, 387; 411/352, 378, 403, 402, 411/366.1, 378.1, 393
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D283,591 S *	4/1986	Swanstrom	D8/387
D391,844 S *	3/1998	Ropponen et al.	D8/382
D392,179 S *	3/1998	Ropponen et al.	D8/387
D627,215 S *	11/2010	Summers	D8/387
D639,647 S *	6/2011	Summers	D8/387
D639,648 S *	6/2011	Summers	D8/387
D639,649 S *	6/2011	Summers	D8/387
D639,650 S *	6/2011	Summers	D8/387
D656,392 S *	3/2012	McKenna	D8/382
8,291,583 B2 *	10/2012	Wang	29/840
D681,434 S *	5/2013	Wang	D8/387

OTHER PUBLICATIONS

Southco, Brochure regarding Captive Fasteners (2006).
Southco, Data Sheet regarding 5T Captive Screw (2008).
Penn Engineering, Bulletin PF (2012) (esp. pp. PF9-10).

* cited by examiner

Primary Examiner — Sheryl Lane

(74) *Attorney, Agent, or Firm* — Richard A. Nebb; Dergosits & Noah, LLP

(57) **CLAIM**

The ornamental design for a captive screw, as shown and described.

DESCRIPTION

FIG. 1 is a side perspective view for a first embodiment of a captive screw with a knurled screw cap in a non-fastened position, with all remaining sides being identical with the exception of the spring, and a driver recess shown in dashed lines.



FIG. 2 is a side perspective view for the first embodiment thereof, shown in a fastened position.

FIG. 3 is a side perspective view for a second embodiment of a captive screw with a smooth, non-knurled screw cap in a non-fastened position, with all remaining sides being identical with the exception of the spring, and a driver recess shown in dashed lines; and,

FIG. 4 is a side perspective view for the second embodiment thereof, shown in a fastened position.

The broken lines represent portions of the article and form no part of the claimed design.

1 Claim, 1 Drawing Sheet






Fig. 1




Fig. 2




Fig. 3




Fig. 4