

US00D729721S

(12) **United States Design Patent**
Fahr-Becker

(10) **Patent No.:** **US D729,721 S**

(45) **Date of Patent:** **** May 19, 2015**

(54) **VEHICLE WHEEL RIM**

(71) Applicant: **AUDI AG**, Ingolstadt (DE)

(72) Inventor: **Stephan Fahr-Becker**, München (DE)

(73) Assignee: **AUDI AG**, Ingolstadt (DE)

(**) Term: **14 Years**

(21) Appl. No.: **29/441,761**

(22) Filed: **Jan. 9, 2013**

(30) **Foreign Application Priority Data**

Jul. 10, 2012 (EM) 002070649-0002
Jul. 10, 2012 (EM) 002070649-0003

(51) **LOC (10) Cl.** **12-16**

(52) **U.S. Cl.**
USPC **D12/211**

(58) **Field of Classification Search**
CPC B60B 7/00; B60B 7/02; B60B 7/04;
B60B 7/01; B60B 7/06; B60B 3/02; B60B
3/04; B60B 3/06; B60B 3/10; B60B 1/00;
B60B 1/08; B60B 1/10; B60B 1/12
USPC D12/204–213
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D567,167 S * 4/2008 Forster D12/211
D589,428 S * 3/2009 Scheu D12/211
D634,691 S * 3/2011 Park D12/211
D644,977 S * 9/2011 Juergens et al. D12/211
D645,389 S * 9/2011 Nissl D12/209
D649,500 S * 11/2011 Baum D12/209
D654,843 S * 2/2012 Futschik et al. D12/211
D655,661 S * 3/2012 Truebsbach D12/211
D659,068 S * 5/2012 Johnson D12/211

D670,632 S * 11/2012 Schweizer D12/211
D671,473 S * 11/2012 Zurian D12/209
D673,104 S * 12/2012 Lemke D12/211
D675,554 S * 2/2013 Nissl D12/211
D682,764 S * 5/2013 Amezketta D12/211
D686,966 S * 7/2013 Pollmann D12/211
D688,188 S * 8/2013 Baum D12/211
D702,614 S * 4/2014 Lemke D12/211

FOREIGN PATENT DOCUMENTS

EM 001826058-0028 2/2011
EM 001826058-0043 2/2011

* cited by examiner

Primary Examiner — Stacia Cadmus

(74) *Attorney, Agent, or Firm* — Lucas & Mercanti, LLP;
Klaus P. Stoffel

(57) **CLAIM**

The ornamental design for a vehicle wheel rim, as shown and described

DESCRIPTION

FIG. 1 is a front view of the vehicle wheel rim of the present invention;
FIG. 2 is a front, left side perspective view thereof;
FIG. 3 is a left side view thereof;
FIG. 4 is a right side view thereof;
FIG. 5 is a bottom view thereof;
FIG. 6 is a top view thereof;
FIG. 7 is a front view of a second embodiment of the vehicle wheel rim of the present invention;
FIG. 8 is a front, left side perspective view thereof;
FIG. 9 is a left side view thereof;
FIG. 10 is a right side view thereof;
FIG. 11 is a bottom view thereof; and,
FIG. 12 is a top view thereof.

1 Claim, 10 Drawing Sheets





Fig. 1



Fig. 2



Fig. 3




Fig. 4




Fig. 5



Fig. 6



Fig. 7



Fig. 8




Fig. 9



Fig. 10



Fig. 11



Fig. 12