

US00D732533S

(12) **United States Design Patent**
Hirota

(10) **Patent No.:** **US D732,533 S**
(45) **Date of Patent:** **** Jun. 23, 2015**

(54) **COORDINATE INPUT DEVICE**

(71) Applicant: **Wacom Co., Ltd.**, Kazo-shi, Saitama (JP)

(72) Inventor: **Masuo Hirota**, Kuki (JP)

(73) Assignee: **Wacom Co., Ltd.**, Kazo-shi (JP)

(**) Term: **14 Years**

(21) Appl. No.: **29/457,735**

(22) Filed: **Jun. 12, 2013**

(30) **Foreign Application Priority Data**

Dec. 17, 2012 (JP) 2012-30708

(51) **LOC (10) Cl.** **14-02**

(52) **U.S. Cl.**
USPC **D14/389**

(58) **Field of Classification Search**

USPC D14/388-390, 341-347, 383, 384, 374,
D14/381, 356; D19/52; 178/18.01,
178/18.03-18.09, 18.11; 345/173-178
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D313,409 S * 1/1991 Chowdhree et al. D14/389
(Continued)

FOREIGN PATENT DOCUMENTS

JP D1142128 S 5/2002
(Continued)

Primary Examiner — Deanna L Pratt

(74) *Attorney, Agent, or Firm* — Christensen O'Connor Johnson Kindness PLLC

(57) **CLAIM**


The ornamental design for a coordinate input device, as shown and described.

DESCRIPTION

FIG. 1 is a bottom left front perspective view of a coordinate input device showing my new design;
FIG. 2 is a front elevation view thereof;
FIG. 3 is a rear elevation view thereof, wherein a pair of short support legs and a pair of long support legs are shown in a retracted position;

FIG. 4 is a left side elevation view thereof;
FIG. 5 is a right side elevation view thereof;
FIG. 6 is a top plan view thereof;
FIG. 7 is a bottom plan view thereof;
FIG. 8 is a rear elevation view thereof, wherein the short support legs are shown in an extended position while the long support legs remain in the retracted position;
FIG. 9 is a left side elevation view thereof;
FIG. 10 is a right side elevation view thereof;
FIG. 11 is a top plan view thereof;
FIG. 12 is a bottom plan view thereof;
FIG. 13 is a rear elevation view thereof, wherein both the short support legs and the long support legs are shown in the extended position;
FIG. 14 is a left side elevation view thereof;
FIG. 15 is a right side elevation view thereof;
FIG. 16 is a top plan view thereof;
FIG. 17 is a bottom plan view thereof;
FIG. 18 is an enlarged cross sectional view along a portion of the line 18-18 illustrated in FIG. 17;
FIG. 19 is a bottom left front perspective view of an alternative embodiment of the coordinate input device shown in FIG. 1;
FIG. 20 is a front elevation view thereof;
FIG. 21 is a rear elevation view thereof, wherein a pair of short support legs and a pair of long support legs are shown in a retracted position;
FIG. 22 is a left side elevation view thereof;
FIG. 23 is a right side elevation view thereof;
FIG. 24 is a top plan view thereof;
FIG. 25 is a bottom plan view thereof;
FIG. 26 is a rear elevation view thereof, wherein the short support legs are shown in an extended position while the long support legs remain in the retracted position;
FIG. 27 is a left side elevation view thereof;
FIG. 28 is a right side elevation view thereof;
FIG. 29 is a top plan view thereof;
FIG. 30 is a bottom plan view thereof;
FIG. 31 is a rear elevation view thereof, wherein both the short support legs and the long support legs are shown in the extended position;
FIG. 32 is a left side elevation view thereof;
FIG. 33 is a right side elevation view thereof;
FIG. 34 is a top plan view thereof;
FIG. 35 is a bottom plan view thereof; and,
FIG. 36 is an enlarged cross sectional view along a portion of the line 36-36 illustrated in FIG. 35.

1 Claim, 22 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

D352,280 S * 11/1994 Calco D14/390
 D359,984 S * 7/1995 Mak D19/113
 D385,857 S * 11/1997 Cohen et al. D14/390
 D395,639 S * 6/1998 Ham et al. D14/389
 D451,505 S * 12/2001 Iseki et al. D14/341
 D466,501 S * 12/2002 Hirota D14/339
 D481,719 S * 11/2003 Okawa et al. D14/341
 6,816,152 B2 * 11/2004 Yanagisawa 345/173
 D501,473 S * 2/2005 Nakata D14/341
 D534,215 S * 12/2006 Nakata D19/113
 D554,640 S * 11/2007 Ponnert et al. D14/388
 D605,194 S 12/2009 Hakoda
 D617,793 S * 6/2010 Chiang et al. D14/341
 D631,043 S * 1/2011 Kell D14/341

D636,768 S 4/2011 Chan
 8,350,813 B2 * 1/2013 Sato 345/168
 8,390,272 B2 * 3/2013 Yokota et al. 324/207.11
 D680,525 S * 4/2013 Deto et al. D14/341
 D684,970 S * 6/2013 Zhang D14/341
 D701,570 S * 3/2014 Fletcher et al. D19/113
 D703,663 S * 4/2014 Piraud D14/341
 D711,370 S * 8/2014 Chen et al. D14/341
 D714,784 S * 10/2014 Park D14/341

FOREIGN PATENT DOCUMENTS

JP D1190089 S 11/2003
 JP D1449033 S 8/2012
 JP D1464170 S 3/2013

* cited by examiner




Fig. 1.




Fig. 2.




Fig. 3.




Fig. 4.




Fig. 5.




Fig. 6.



Fig. 7.




Fig. 8.



Fig. 9.




Fig. 10.



Fig. 11.




Fig. 12.






Fig. 13.



Fig. 14.



Fig. 15.






Fig. 19.




Fig. 20.




Fig. 21.




Fig. 22.




Fig. 23.




Fig. 24.




Fig. 25.




Fig. 26.



Fig. 27.



Fig. 28.






Fig. 31.





Fig. 32.



Fig. 33.



36.

36.



Fig. 36.