



US00D732660S

(12) **United States Design Patent**  
**Ohashi**

(10) **Patent No.:** **US D732,660 S**  
(45) **Date of Patent:** **\*\* Jun. 23, 2015**

(54) **SAFETY DEVICE FOR INDWELLING NEEDLE**

(71) Applicant: **Terumo Kabushiki Kaisha**, Shibuya-ku, Tokyo (JP)

(72) Inventor: **Hiroataka Ohashi**, Tokyo (JP)

(73) Assignee: **Terumo Kabushiki Kaisha**, Shibuya-ku, Tokyo (JP)

(\*\*) Term: **14 Years**

(21) Appl. No.: **29/509,240**

(22) Filed: **Nov. 14, 2014**

**Related U.S. Application Data**

(63) Continuation of application No. 29/428,713, filed on Aug. 2, 2012, now Pat. No. Des. 719,256.

(30) **Foreign Application Priority Data**

Feb. 2, 2012 (JP) ..... 2012-002138

(51) **LOC (10) Cl.** ..... **24-02**

(52) **U.S. Cl.**  
USPC ..... **D24/112**

(58) **Field of Classification Search**  
USPC ..... 604/264, 167.1, 164.2, 164.4, 164.5, 604/164.7, 164.8, 263, 268, 243, 110, 158, 604/192, 272, 162, 198, 164.09, 164.01, 604/164.07, 164.08, 164.11, 164.12; D24/112, 113, 114, 108, 133, 186, 130, D24/127; 600/139

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

5,000,740 A 3/1991 Ducharme et al.  
5,108,374 A 4/1992 Lemieux  
5,127,905 A 7/1992 Lemieux

5,704,919 A 1/1998 Kraus et al.  
6,379,332 B1 4/2002 Van Landuyt  
6,676,638 B2 1/2004 Takagi et al.  
6,770,059 B1 8/2004 Spinks et al.  
6,972,002 B2 12/2005 Thorne  
7,255,685 B2\* 8/2007 Pressly et al. .... 604/164.08  
7,351,225 B2 4/2008 Takagi et al.  
7,736,342 B2 6/2010 Abriles et al.  
D640,785 S 6/2011 Lee  
D655,406 S 3/2012 Ma et al.  
D699,341 S\* 2/2014 Clark ..... D24/112  
8,702,658 B2\* 4/2014 Spearman ..... 604/168.01

(Continued)

*Primary Examiner* — Sheryl Lane

*Assistant Examiner* — Ieisha Price

(74) *Attorney, Agent, or Firm* — Banner & Witcoff, Ltd.

(57) **CLAIM**

The ornamental design for the safety device for indwelling needle, as shown and described.

**DESCRIPTION**

FIG. 1 is a front perspective view of a safety device for indwelling needle showing my new design;

FIG. 2 is a front view thereof;

FIG. 3 is a rear view thereof;

FIG. 4 is a left side view thereof;

FIG. 5 is a right side view thereof;

FIG. 6 is a top plan view thereof;

FIG. 7 is a bottom view thereof;

FIG. 8 is a top plan view showing a state where an inner case is slid;

FIG. 9 is a front view showing a state where an inner case is slid;


FIG. 10 is a perspective view shown in compressed condition;

FIG. 11 is another perspective view shown in compressed condition; and,

FIG. 12 is a perspective view thereof shown in extended condition.

The broken lines in FIGS. 1-12 illustrate the environment of the claimed design and form no part thereof.

**1 Claim, 7 Drawing Sheets**



(56)

**References Cited**

U.S. PATENT DOCUMENTS

D719,255 S *	12/2014	Ohashi .....	D24/112	2004/0019329 A1 *	1/2004	Erskine .....	604/164.12
D719,256 S *	12/2014	Ohashi .....	D24/112	2004/0230164 A1	11/2004	Spinks et al.	
8,900,199 B2 *	12/2014	Kawai et al. ....	604/198	2006/0041231 A1	2/2006	Pressly et al.	
2003/0083620 A1 *	5/2003	Luther et al. ....	604/164.07	2008/0300543 A1 *	12/2008	Abriles et al. ....	604/162
				2011/0306933 A1 *	12/2011	Djordjevic et al. ....	604/164.08
				2013/0172820 A1	7/2013	Spearman	

\* cited by examiner




Fig. 1

Fig. 2




Fig. 3



Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10





Fig. 11








Fig. 12