

US00D732731S

(12) **United States Design Patent**
Wang

(10) **Patent No.:** **US D732,731 S**
(45) **Date of Patent:** **** Jun. 23, 2015**

(54) **ELECTRONIC FIXTURE**

(76) Inventor: **James Jen-Ho Wang**, Phoenix, AZ (US)

(**) Term: **14 Years**

(21) Appl. No.: **29/421,678**

(22) Filed: **Sep. 4, 2012**

(51) **LOC (10) Cl.** **26-99**

(52) **U.S. Cl.**
USPC **D26/127; D26/73**

(58) **Field of Classification Search**

USPC D26/4, 7, 16, 19, 24, 26, 32, 51, 57, 61,
D26/67, 72-74, 80-86, 88-91, 93, 94, 98,
D26/101, 104, 113, 118-120, 125, 127, 128,
D26/138, 147, 156; 362/122, 145, 147,
362/249.06, 249.14, 249.18, 257, 296.01,
362/310, 362, 404-408, 453, 458, 565, 567,
362/644, 653, 806, 808, 811; D23/367

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D196,259 S *	9/1963	Dwyer		D26/127
D292,762 S *	11/1987	Williamson		D6/451
D397,473 S *	8/1998	Keen		D26/127
D410,756 S *	6/1999	Kleinberg		D26/9
5,947,582 A *	9/1999	Huang		362/122
D422,350 S *	4/2000	Wu		D23/367
6,364,501 B1 *	4/2002	Tai		362/122
D509,315 S *	9/2005	Weiser et al.		D26/101
D511,018 S *	10/2005	Sooferian		D26/67
D604,826 S *	11/2009	Lesniak et al.		D23/367
D614,279 S *	4/2010	Lesniak et al.		D23/367

D630,791 S *	1/2011	Wanders		D26/73
D643,966 S *	8/2011	Postelmans		D26/88
D682,453 S *	5/2013	Glenn		D26/73
D683,912 S *	6/2013	Muhr et al.		D30/125
2007/0159813 A1 *	7/2007	Husbands		362/122
2009/0219711 A1 *	9/2009	Webb		362/122
2010/0097790 A1 *	4/2010	Tseng		362/122

* cited by examiner

Primary Examiner — Cynthia Ramirez

Assistant Examiner — Llorellys Martinez-Rivera

(74) *Attorney, Agent, or Firm* — Edward J. Mischen

(57) **CLAIM**

The ornamental design for an electronic fixture, as shown and described.

DESCRIPTION

FIG. 1 is a front elevation view of an electronic fixture showing my new design;


FIG. 2 is a rear elevation view thereof; and,

FIG. 3 is a side perspective view thereof.

The electronic fixture houses electronic components, and is typically attached to a ceiling or wall. Components may be inserted through the larger opening on the rear surface of the electronic fixture. The two smaller openings on each side of the larger opening facilitate the attachment of the fixture to external components or to a ceiling or wall.

The broken line portions shown in FIGS. 2 and 3 illustrate portions of the electronic fixture that form no part of the claimed design.

1 Claim, 2 Drawing Sheets






Fig. 1




Fig. 2




Fig. 3