



US00D733297S

(12) **United States Design Patent**
Harrison et al.

(10) **Patent No.:** **US D733,297 S**
(45) **Date of Patent:** **** Jun. 30, 2015**

(54) **HANDLE FOR SUTURING INSTRUMENT**

(71) Applicant: **Anchor Orthopedics XT Inc.**,
Mississauga (CA)

(72) Inventors: **Robert Harrison**, Milton (CA); **Steve Copeland**, Barrie (CA); **Jonathan Liberty**, Newmarket (CA); **Jeffery Arnett**, Gilbert, AZ (US); **Dylan Hushka**, Niwot, CO (US); **Neil Godara**, Milton (CA)

(73) Assignee: **ANCHER ORTHOPEDICS XT INC.**,
Mississauga, Ontario (CA)

(**) Term: **14 Years**

(21) Appl. No.: **29/489,200**

(22) Filed: **Apr. 28, 2014**

Related U.S. Application Data

(63) Continuation of application No. 29/447,624, filed on Mar. 5, 2013, now Pat. No. Des. 706,928.

(51) **LOC (10) Cl.** **24-02**

(52) **U.S. Cl.**
USPC **D24/145**

(58) **Field of Classification Search**
USPC D24/133, 145-147; D8/49-51, 68;
227/175.1, 180.1, 901-902; 606/139,
606/142-143, 170
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D282,400 S * 1/1986 Guy et al. D24/145
D284,219 S * 6/1986 Green et al. D24/145

(Continued)

Primary Examiner — Wan Laymon

(74) *Attorney, Agent, or Firm* — Nir Lipshitz; Glenn Arnold



(57) **CLAIM**

The ornamental design for a handle for a suturing instrument, as shown and described.

DESCRIPTION

FIG. 1 is a top, front, left perspective view of a handle for a suturing instrument, with the trigger in a first position, showing our new design;
FIG. 2 is a bottom, front, right perspective view of the handle for a suturing instrument of FIG. 1;
FIG. 3 is a left side view of the handle for a suturing instrument of FIG. 1;
FIG. 4 is a right side view of the handle for a suturing instrument of FIG. 1;
FIG. 5 is a top side view of the handle for a suturing instrument of FIG. 1;
FIG. 6 is a bottom side view of the handle for a suturing instrument of FIG. 1;
FIG. 7 is a front side view of the handle for a suturing instrument of FIG. 1;
FIG. 8 is a rear side view of the handle for a suturing instrument of FIG. 1;
FIG. 9 is a top, front, left perspective view of the handle for a suturing instrument of FIG. 1, showing a shaft of the suturing instrument in dashed outline;
FIG. 10 is a top, front, left perspective exploded view of the handle for a suturing instrument;
FIG. 11 is a top, front, left perspective view of the handle for a suturing instrument of FIG. 1, with the trigger in an alternate position;
FIG. 12 is a left side view of the handle for a suturing instrument of FIG. 11;
FIG. 13 is a top, front, left perspective view of the handle for a suturing instrument of FIG. 1, with the trigger in a second alternate position; and,
FIG. 14 is a left side view of the handle for a suturing instrument of FIG. 13.
The broken lines immediately adjacent the shaded areas represent the bounds of the claimed design while all other broken lines are directed to the environment and are for illustrative purposes only; the broken lines form no part of the claimed design.

1 Claim, 12 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

D327,323	S	*	6/1992	Hunt	D24/145	6,036,667	A	*	3/2000	Manna et al.	606/170
5,601,573	A	*	2/1997	Fogelberg et al.	606/143	D502,994	S	*	3/2005	Blake, III	D24/145
RE35,525	E	*	6/1997	Stefanchik et al.	606/142	8,652,152	B2	*	2/2014	Aranyi et al.	606/143
5,830,221	A	*	11/1998	Stein et al.	606/142	8,728,098	B2	*	5/2014	Daniel et al.	606/143
							2013/0310849	A1	*	11/2013	Malkowski	606/142

* cited by examiner




FIG.1




FIG.2




FIG.3




FIG.4




FIG.5




FIG.6




FIG. 7




FIG. 8





FIG.9






FIG.11




FIG.12




FIG.13




FIG.14