



US00D733710S

(12) **United States Design Patent**  
**Huebner**

(10) **Patent No.:** **US D733,710 S**  
(45) **Date of Patent:** **\*\* Jul. 7, 2015**

- (54) **COORDINATE INPUT DEVICE**
- (71) Applicant: **Wacom Co., Ltd.**, Kazo-shi, Saitama (JP)
- (72) Inventor: **Volker Huebner**, Erkrath (DE)
- (73) Assignee: **Wacom Co., Ltd.**, Kazo-shi (JP)
- (\*\*) Term: **14 Years**
- (21) Appl. No.: **29/508,258**
- (22) Filed: **Nov. 4, 2014**

D408,794 S 4/1999 Ogasawara  
 D460,448 S \* 7/2002 Matsumoto ..... D14/346  
 D464,961 S \* 10/2002 Sogabe ..... D14/346

(Continued)

FOREIGN PATENT DOCUMENTS

EM 001322168-0001 4/2012  
 EM 001361851-0019 4/2013

(Continued)

OTHER PUBLICATIONS

“Motion J3600,” © 2013 Motion Computing, Inc., Product Specifications, 2 pages.

*Primary Examiner* — Barbara Fox

(74) *Attorney, Agent, or Firm* — Christensen O’Connor Johnson Kindness PLLC

**Related U.S. Application Data**

(63) Continuation of application No. 29/460,813, filed on Jul. 15, 2013, now Pat. No. Des. 719,161.

**Foreign Application Priority Data**

(30) Jan. 18, 2013 (JP) ..... 2013-000804

(51) **LOC (10) Cl.** ..... **14-02**

(52) **U.S. Cl.**  
USPC ..... **D14/390; D14/341**

(58) **Field of Classification Search**  
 USPC ..... D14/341–347, 137, 138 R, 138 AA,  
 D14/138 C, 138 G, 496, 203.1, 203.3, 203.4,  
 D14/203.7, 129, 130, 147, 218, 242, 248,  
 D14/389, 388, 426, 420; D10/65, 104.1;  
 D18/6–7; D21/324, 329, 330;  
 455/556.1, 556.2, 566, 575.1, 90.3;  
 379/433.04, 433.01, 433.06, 916;  
 345/173, 901, 905; 361/679.26, 679.3,  
 361/679.55, 679.56

See application file for complete search history.

**References Cited**

U.S. PATENT DOCUMENTS

D333,125 S \* 2/1993 Komada et al. .... D14/390

(57) **CLAIM**


The ornamental design for a coordinate input device, as shown and described.

**DESCRIPTION**

FIG. 1 is a bottom front right perspective view of a coordinate input device according to my new design;  
 FIG. 2 is a front view of the coordinate input device of FIG. 1;  
 FIG. 3 is a rear view of the coordinate input device of FIG. 1;  
 FIG. 4 is a left side view of the coordinate input device of FIG. 1;  
 FIG. 5 is a right side view of the coordinate input device of FIG. 1;  
 FIG. 6 is a top plan view of the coordinate input device of FIG. 1; and,  
 FIG. 7 is a bottom plan view of the coordinate input device of FIG. 1.

The broken lines shown in the drawings represent portions of the coordinate input device that form no part of the claimed design.

**1 Claim, 7 Drawing Sheets**



(56)

References Cited

U.S. PATENT DOCUMENTS


D495,695 S \* 9/2004 Yugaya ..... D14/346  
 D524,308 S \* 7/2006 Lai ..... D14/346  
 D597,067 S \* 7/2009 Oh et al. .... D14/203.7  
 D597,523 S \* 8/2009 Zhang et al. .... D14/203.7  
 D602,488 S \* 10/2009 Jiang et al. .... D14/341  
 D608,327 S \* 1/2010 Cigliano et al. .... D14/138 AD  
 D613,286 S \* 4/2010 Lee et al. .... D14/341  
 D625,726 S \* 10/2010 Crisp et al. .... D14/389  
 D625,728 S \* 10/2010 Crisp et al. .... D14/390  
 D629,401 S \* 12/2010 Crisp et al. .... D14/390  
 D635,952 S 4/2011 Park  
 D638,396 S \* 5/2011 Finnegan ..... D14/203.7  
 D649,968 S 12/2011 Li  
 D663,298 S 7/2012 Song  
 D664,954 S 8/2012 Kim  
 D666,620 S \* 9/2012 Harper et al. .... D14/448  
 D670,287 S \* 11/2012 Shimizu et al. .... D14/341  
 D671,086 S 11/2012 Yu  
 D671,117 S 11/2012 Harper  
 D680,512 S 4/2013 Lu  
 D681,011 S \* 4/2013 Cheung et al. .... D14/218  
 D689,481 S 9/2013 Song  
 D689,491 S \* 9/2013 Halsinger et al. .... D14/389

D689,492 S \* 9/2013 Halsinger et al. .... D14/389  
 D689,499 S 9/2013 Chen  
 D690,696 S 10/2013 Jonsson  
 D690,697 S 10/2013 Jonsson  
 D690,700 S \* 10/2013 Jonsson et al. .... D14/390  
 D697,507 S \* 1/2014 Yu et al. .... D14/341  
 D703,203 S 4/2014 Hong  
 D706,774 S 6/2014 Park  
 D712,402 S 9/2014 Park  
 D712,403 S 9/2014 Park  
 D712,899 S 9/2014 Park  
 D714,783 S 10/2014 Takizawa  
 D714,784 S 10/2014 Park  
 D718,266 S \* 11/2014 Zhang et al. .... D14/138 G  
 D719,161 S \* 12/2014 Huebner ..... D14/389  
 2008/0102688 A1 \* 5/2008 Chen ..... 439/422  
 2013/0161179 A1 \* 6/2013 Tamura et al. .... 200/600  
 2014/0185218 A1 7/2014 Chen  
 2014/0263930 A1 \* 9/2014 Huebner ..... 248/558


FOREIGN PATENT DOCUMENTS

JP D1446815 S 7/2012  
 JP D1450316 S 9/2012  
 JP D1450317 S 9/2012


\* cited by examiner




*Fig. 1.*




*Fig. 2.*




*Fig. 3.*



*Fig. 4.*




*Fig. 5.*



*Fig. 6.*





*Fig. 7.*

UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : D733,710 S  
APPLICATION NO. : 29/508258  
DATED : July 7, 2015  
INVENTOR(S) : V. Huebner

Page 1 of 9

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Delete the title page and substitute therefore with the attached title page consisting of the corrected illustrative figures.

Delete Drawing Sheets 1-7 and substitute therefore with the attached Drawing Sheets 1-7.

Signed and Sealed this  
Fifteenth Day of August, 2017



Joseph Matal  
*Performing the Functions and Duties of the  
Under Secretary of Commerce for Intellectual Property and  
Director of the United States Patent and Trademark Office*

(12) **United States Design Patent**  
**Huebner**

(10) **Patent No.:** **US D733,710 S**  
(45) **Date of Patent:** **\*\* Jul. 7, 2015**

(54) **COORDINATE INPUT DEVICE**

(71) Applicant: **Wacom Co., Ltd., Kazo-shi, Saitama (JP)**

(72) Inventor: **Volker Huebner, Erkrath (DE)**

(73) Assignee: **Wacom Co., Ltd., Kazo-shi (JP)**

(\*\*) Term: **14 Years**

(21) Appl. No.: **29/508,258**

(22) Filed: **Nov. 4, 2014**

**Related U.S. Application Data**

(63) Continuation of application No. 29/460,813, filed on Jul. 15, 2013, now Pat. No. Des. 719,161.

(30) **Foreign Application Priority Data**

Jan. 18, 2013 (JP) ..... 2013-000804

(51) **LOC (10) CL.** ..... **14-02**

(52) **U.S. CL.**  
USPC ..... **D14/390; D14/341**

(58) **Field of Classification Search**

USPC ..... D14/341-347, 137, 138 R, 138 A.A, D14/138 C, 138 G, 496, 203.1, 203.3, 203.4, D14/203.7, 129, 130, 147, 218, 242, 248, D14/389, 388, 426, 420; D10/65, 104.1; D18/6-7; D21/324, 329, 330; 455/556.1, 556.2, 566, 575.1, 90.3; 379/433.04, 433.01, 433.06, 916; 345/173, 901, 905; 361/679.26, 679.3, 361/679.55, 679.56

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

D333,125 S \* 2/1993 Komada et al. .... D14/390

D468,794 S 4/1999 Ogasawara  
D460,448 S \* 7/2002 Matsumoto ..... D14/346  
D464,961 S \* 10/2002 Sogabe ..... D14/346  
(Continued)

**FOREIGN PATENT DOCUMENTS**

EM 001322168-0001 4/2012  
EM 001361851-0019 4/2013

(Continued)

**OTHER PUBLICATIONS**

"Motion J3600." © 2013 Motion Computing, Inc., Product Specifications, 2 pages.

*Primary Examiner* — Barbara Fox

(74) *Attorney, Agent, or Firm* Christensen O'Connor Johnson Kindness PLLC

(57) **CLAIM**

The ornamental design for a coordinate input device, as shown and described.

**DESCRIPTION**

FIG. 1 is a bottom front right perspective view of a coordinate input device according to my new design;

FIG. 2 is a front view of the coordinate input device of FIG. 1;

FIG. 3 is a rear view of the coordinate input device of FIG. 1;

FIG. 4 is a left side view of the coordinate input device of FIG. 1;



FIG. 5 is a right side view of the coordinate input device of FIG. 1;


FIG. 6 is a top plan view of the coordinate input device of FIG. 1; and,

FIG. 7 is a bottom plan view of the coordinate input device of FIG. 1.


The broken lines shown in the drawings represent portions of the coordinate input device that form no part of the claimed design.

**1 Claim, 7 Drawing Sheets**





*Fig. 1.*




*Fig. 2.*

U.S. Patent

Jul. 7, 2015

Sheet 3 of 7


D733,710 S



*Fig. 3.*



*Fig. 4.*



*Fig. 5.*




U.S. Patent

Jul. 7, 2015

Sheet 6 of 7

D733,710 S




*Fig. 6.*

U.S. Patent

Jul. 7, 2015

Sheet 7 of 7

D733,710 S



*Fig. 7.*