



US00D733710S

(12) **United States Design Patent**
Huebner

(10) **Patent No.:** **US D733,710 S**
(45) **Date of Patent:** **** Jul. 7, 2015**

- (54) **COORDINATE INPUT DEVICE**
- (71) Applicant: **Wacom Co., Ltd.**, Kazo-shi, Saitama (JP)
- (72) Inventor: **Volker Huebner**, Erkrath (DE)
- (73) Assignee: **Wacom Co., Ltd.**, Kazo-shi (JP)
- (**) Term: **14 Years**
- (21) Appl. No.: **29/508,258**
- (22) Filed: **Nov. 4, 2014**

D408,794 S 4/1999 Ogasawara
 D460,448 S * 7/2002 Matsumoto D14/346
 D464,961 S * 10/2002 Sogabe D14/346

(Continued)

FOREIGN PATENT DOCUMENTS

EM 001322168-0001 4/2012
 EM 001361851-0019 4/2013

(Continued)

OTHER PUBLICATIONS

“Motion J3600,” © 2013 Motion Computing, Inc., Product Specifications, 2 pages.

Primary Examiner — Barbara Fox

(74) *Attorney, Agent, or Firm* — Christensen O’Connor Johnson Kindness PLLC

Related U.S. Application Data

(63) Continuation of application No. 29/460,813, filed on Jul. 15, 2013, now Pat. No. Des. 719,161.

Foreign Application Priority Data

(30) Jan. 18, 2013 (JP) 2013-000804

(51) **LOC (10) Cl.** **14-02**

(52) **U.S. Cl.**
USPC **D14/390; D14/341**

(58) **Field of Classification Search**
 USPC D14/341–347, 137, 138 R, 138 AA,
 D14/138 C, 138 G, 496, 203.1, 203.3, 203.4,
 D14/203.7, 129, 130, 147, 218, 242, 248,
 D14/389, 388, 426, 420; D10/65, 104.1;
 D18/6–7; D21/324, 329, 330;
 455/556.1, 556.2, 566, 575.1, 90.3;
 379/433.04, 433.01, 433.06, 916;
 345/173, 901, 905; 361/679.26, 679.3,
 361/679.55, 679.56

See application file for complete search history.

References Cited

U.S. PATENT DOCUMENTS

(56) D333,125 S * 2/1993 Komada et al. D14/390

(57) **CLAIM**


The ornamental design for a coordinate input device, as shown and described.

DESCRIPTION

FIG. 1 is a bottom front right perspective view of a coordinate input device according to my new design;
 FIG. 2 is a front view of the coordinate input device of FIG. 1;
 FIG. 3 is a rear view of the coordinate input device of FIG. 1;
 FIG. 4 is a left side view of the coordinate input device of FIG. 1;
 FIG. 5 is a right side view of the coordinate input device of FIG. 1;
 FIG. 6 is a top plan view of the coordinate input device of FIG. 1; and,
 FIG. 7 is a bottom plan view of the coordinate input device of FIG. 1.

The broken lines shown in the drawings represent portions of the coordinate input device that form no part of the claimed design.

1 Claim, 7 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

D495,695 S * 9/2004 Yugaya D14/346
 D524,308 S * 7/2006 Lai D14/346
 D597,067 S * 7/2009 Oh et al. D14/203.7
 D597,523 S * 8/2009 Zhang et al. D14/203.7
 D602,488 S * 10/2009 Jiang et al. D14/341
 D608,327 S * 1/2010 Cigliano et al. D14/138 AD
 D613,286 S * 4/2010 Lee et al. D14/341
 D625,726 S * 10/2010 Crisp et al. D14/389
 D625,728 S * 10/2010 Crisp et al. D14/390
 D629,401 S * 12/2010 Crisp et al. D14/390
 D635,952 S 4/2011 Park
 D638,396 S * 5/2011 Finnegan D14/203.7
 D649,968 S 12/2011 Li
 D663,298 S 7/2012 Song
 D664,954 S 8/2012 Kim
 D666,620 S * 9/2012 Harper et al. D14/448
 D670,287 S * 11/2012 Shimizu et al. D14/341
 D671,086 S 11/2012 Yu
 D671,117 S 11/2012 Harper
 D680,512 S 4/2013 Lu
 D681,011 S * 4/2013 Cheung et al. D14/218
 D689,481 S 9/2013 Song
 D689,491 S * 9/2013 Halsinger et al. D14/389

D689,492 S * 9/2013 Halsinger et al. D14/389
 D689,499 S 9/2013 Chen
 D690,696 S 10/2013 Jonsson
 D690,697 S 10/2013 Jonsson
 D690,700 S * 10/2013 Jonsson et al. D14/390
 D697,507 S * 1/2014 Yu et al. D14/341
 D703,203 S 4/2014 Hong
 D706,774 S 6/2014 Park
 D712,402 S 9/2014 Park
 D712,403 S 9/2014 Park
 D712,899 S 9/2014 Park
 D714,783 S 10/2014 Takizawa
 D714,784 S 10/2014 Park
 D718,266 S * 11/2014 Zhang et al. D14/138 G
 D719,161 S * 12/2014 Huebner D14/389
 2008/0102688 A1 * 5/2008 Chen 439/422
 2013/0161179 A1 * 6/2013 Tamura et al. 200/600
 2014/0185218 A1 7/2014 Chen
 2014/0263930 A1 * 9/2014 Huebner 248/558

FOREIGN PATENT DOCUMENTS

JP D1446815 S 7/2012
 JP D1450316 S 9/2012
 JP D1450317 S 9/2012

* cited by examiner




Fig. 1.




Fig. 2.




Fig. 3.




Fig. 4.




Fig. 5.




Fig. 6.




Fig. 7.

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : D733,710 S
APPLICATION NO. : 29/508258
DATED : July 7, 2015
INVENTOR(S) : V. Huebner

Page 1 of 9

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Delete the title page and substitute therefore with the attached title page consisting of the corrected illustrative figures.

Delete Drawing Sheets 1-7 and substitute therefore with the attached Drawing Sheets 1-7.

Signed and Sealed this
Fifteenth Day of August, 2017



Joseph Matal
*Performing the Functions and Duties of the
Under Secretary of Commerce for Intellectual Property and
Director of the United States Patent and Trademark Office*

(12) **United States Design Patent**
Huebner

(10) **Patent No.:** **US D733,710 S**
(45) **Date of Patent:** **** Jul. 7, 2015**

(54) **COORDINATE INPUT DEVICE**
(71) Applicant: **Wacom Co., Ltd., Kazo-shi, Saitama**
(JP)
(72) Inventor: **Volker Huebner, Erkrath (DE)**
(73) Assignee: **Wacom Co., Ltd., Kazo-shi (JP)**
(**) Term: **14 Years**
(21) Appl. No.: **29/508,258**
(22) Filed: **Nov. 4, 2014**

Related U.S. Application Data

(63) Continuation of application No. 29/460,813, filed on Jul. 15, 2013, now Pat. No. Des. 719,161.

(30) **Foreign Application Priority Data**

Jan. 18, 2013 (JP) 2013-000804

(51) **LOC (10) CL.** **14-02**

(52) **U.S. CL.**
USPC **D14/390; D14/341**

(58) **Field of Classification Search**

USPC D14/341-347, 137, 138 R, 138 A.A,
D14/138 C, 138 G, 496, 203.1, 203.3, 203.4,
D14/203.7, 129, 130, 147, 218, 242, 248,
D14/389, 388, 426, 420; D10/65, 104.1;
D18/6-7; D21/324, 329, 330;
455/556.1, 556.2, 566, 575.1, 90.3;
379/433.04, 433.01, 433.06, 916;
345/173, 901, 905; 361/679.26, 679.3,
361/679.55, 679.56

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D333,125 S * 2/1993 Komada et al. D14/390

D468,794 S 4/1999 Ogasawara
D460,448 S * 7/2002 Matsumoto D14/346
D464,961 S * 10/2002 Sogabe D14/346
(Continued)

FOREIGN PATENT DOCUMENTS

EM 001322168-0001 4/2012
EM 001361851-0019 4/2013

(Continued)

OTHER PUBLICATIONS

"Motion J3600." © 2013 Motion Computing, Inc., Product Specifications, 2 pages.

Primary Examiner — Barbara Fox

(74) *Attorney, Agent, or Firm* Christensen O'Connor Johnson Kindness PLLC

(57) **CLAIM**

The ornamental design for a coordinate input device, as shown and described.

DESCRIPTION

FIG. 1 is a bottom front right perspective view of a coordinate input device according to my new design;

FIG. 2 is a front view of the coordinate input device of FIG. 1;

FIG. 3 is a rear view of the coordinate input device of FIG. 1;

FIG. 4 is a left side view of the coordinate input device of FIG. 1;



FIG. 5 is a right side view of the coordinate input device of FIG. 1;

FIG. 6 is a top plan view of the coordinate input device of FIG. 1; and,

FIG. 7 is a bottom plan view of the coordinate input device of FIG. 1.

The broken lines shown in the drawings represent portions of the coordinate input device that form no part of the claimed design.

1 Claim, 7 Drawing Sheets






Fig. 1.




Fig. 2.

U.S. Patent

Jul. 7, 2015

Sheet 3 of 7

D733,710 S




Fig. 3.




Fig. 4.



Fig. 5.

U.S. Patent

Jul. 7, 2015

Sheet 6 of 7

D733,710 S




Fig. 6.

U.S. Patent

Jul. 7, 2015

Sheet 7 of 7

D733,710 S



Fig. 7.