



US00D737154S

(12) **United States Design Patent**  
**Jacoby et al.**

(10) **Patent No.:** **US D737,154 S**  
(45) **Date of Patent:** **\*\* Aug. 25, 2015**

(54) **TEMPERATURE CONTROL DEVICE**

(71) Applicant: **Lutron Electronics Co., Inc.**,  
Coopersburg, PA (US)

(72) Inventors: **Elliot G. Jacoby**, Glenside, PA (US);  
**Jason C. Killo**, Emmaus, PA (US); **Brad**  
**Michael Kreschollek**, Bethlehem, PA  
(US)

(73) Assignee: **Lutron Electronics Co., Inc.**,  
Coopersburg, PA (US)

(\*\*) Term: **14 Years**

(21) Appl. No.: **29/481,501**

(22) Filed: **Feb. 6, 2014**

(51) **LOC (10) Cl.** ..... **10-04**

(52) **U.S. Cl.**  
USPC ..... **D10/50**

(58) **Field of Classification Search**  
USPC ..... D10/49-50, 103; D13/162; 55/279,  
55/DIG. 7; 62/176.6, 125-130, 78, 180,  
62/186; 73/23.2, 23.34, 31.01, 31.02, 431,  
73/170.16-170.19, 170.21-170.25,  
73/863.12, 29.02, 335.01-335.14;  
220/3.2; 236/46 R, 47, 94, 44 C, 44 R,  
236/49.3, 44 A, 96, 1 B, 1 C, 1 E, 1 EA, 1 EB,  
236/1 F, 1 G, 1 H, 9 R; 337/112, 327, 360;  
340/602, 627, 632, 634; 349/56-72;  
454/229, 239, 256, 257, 258; 700/18,  
700/159, 181, 276, 277, 278  
CPC ..... F23N 5/20; F23N 5/203; F23N 5/206;  
F23N 5/18; F23N 5/184; F23N 5/187; F23N  
5/22; F23N 2025/12; F23N 2041/02; F24F  
11/00; F24F 11/0012; F24F 11/0009; F24F  
11/001; F24F 2011/0057; F24F 2011/0073;  
F24F 2011/0091

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,316,256 A \* 2/1982 Hendricks et al. .... D10/50  
D309,268 S \* 7/1990 Wada et al. .... D10/50

(Continued)

OTHER PUBLICATIONS

U.S. Appl. No. 29/515,919 of Elliot G. Jacoby et al. filed Jan. 28,  
2015 (unpublished).

U.S. Appl. No. 29/515,921 of Elliot G. Jacoby et al. filed Jan. 28,  
2015 (unpublished).

(Continued)

*Primary Examiner* — Antoine D Davis

(74) *Attorney, Agent, or Firm* — Saidman DesignLaw  
Group, LLC

(57) **CLAIM**

We claim the ornamental design for a temperature control  
device, as shown and described.

**DESCRIPTION**

FIG. 1 is a perspective view of a temperature control device  
according to a first embodiment of our new design.

FIG. 2 is a front view thereof.

FIG. 3 is a left side view thereof.

FIG. 4 is a right side view thereof.

FIG. 5 is a top view thereof.


FIG. 6 is a bottom view thereof.

FIG. 7 is a perspective view of a temperature control device  
according to a second embodiment of our new design; and,  
FIG. 8 is a front view thereof, the left side, right side, top, and  
bottom views, respectively, of the second embodiment being  
identical to the left side, right side, top, and bottom views of  
the first embodiment.

The rear views form no part of the design and are omitted. The  
portions of the drawings appearing in broken line are for  
environment only and do not form a part of the claimed  
design.

The disclosure of the ornamental design shown in the accom-  
panying drawings herein includes embodiments in which one  
or more of the elements depicted in solid lines may be reduced  
to broken lines.

**1 Claim, 6 Drawing Sheets**



(56)

**References Cited**

U.S. PATENT DOCUMENTS

D310,340 S \* 9/1990 Wada et al. .... D10/50  
D364,573 S \* 11/1995 Pearsall ..... D10/50  
D649,123 S 11/2011 Jacoby et al.  
D717,742 S \* 11/2014 Larkin et al. .... D13/162  
2010/0229089 A1 \* 9/2010 Narita ..... 715/702

OTHER PUBLICATIONS

U.S. Appl. No. 29/515,922 of Elliot G. Jacoby et al. filed Jan. 28, 2015 (unpublished).

U.S. Appl. No. 29/515,924 of Elliot G. Jacoby et al. filed Jan. 28, 2015 (unpublished).

\* cited by examiner




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8